

ADN436


ELECTROMAGNETIC PULSE/TRANSIENT THREAT TESTING OF
PROTECTION DEVICES FOR (U) ELECTROSPACE SYSTEMS INC
ARLINGTON VA D BODSON ET AL 31 OCT 85


172

UNCLASSIFIED

NCS-T1B-85-10-VOL-3-SEC-5 DCA100-85-C-0010 F/G 20/14

NL






MICROCOPY RESOLUTION TEST CHART
NATIONAL BUREAU OF STANDARDS-1963-A

2

NCS TIB 85-10



NATIONAL COMMUNICATIONS SYSTEM

VOLUME III

TEST DATA

ELECTROMAGNETIC PULSE TESTING
OF PROTECTION DEVICES

SECTION 5

EQUIPMENT AND DEVICES
OSCILLOSCOPE PHOTOGRAPHS


OCTOBER 1985

This document has been approved
for public release and sale; its
distribution is unlimited.

DTIC
ELECTE
FEB 20 1986
S D E

AD-A164 436

86 2 20 038



REPORT DOCUMENTATION PAGE

| | | | | | |
|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------|-----------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------|-----------------------------|
| 1a REPORT SECURITY CLASSIFICATION Unclassified | | | 1b RESTRICTIVE MARKINGS None | | |
| 2a SECURITY CLASSIFICATION AUTHORITY | | | 3 DISTRIBUTION AVAILABILITY OF REPORT Approved for public release distribution unlimited | | |
| 2b DECLASSIFICATION/DOWNGRADING SCHEDULE | | | | | |
| 4 PERFORMING ORGANIZATION REPORT NUMBER(S) NCS TIB 85-10, Vol. III, Section 5 | | | 5 MONITORING ORGANIZATION REPORT NUMBER(S) | | |
| 6a NAME OF PERFORMING ORGANIZATION Electrospace Systems, Inc. | | 6b OFFICE SYMBOL (If applicable) | | 7a NAME OF MONITORING ORGANIZATION National Communications System Technology & Standards | |
| 6c ADDRESS (City, State, and ZIP Code) 1725 S. Jefferson Davis Hwy., Suite 501 Arlington, VA 22202-0668 | | | 7b ADDRESS (City, State, and ZIP Code) Washington, D.C. 20305-2010 | | |
| 8a NAME OF FUNDING/SPONSORING ORGANIZATION National Communications System | | 8b OFFICE SYMBOL (If applicable) NCS-TS | | 9. PROCUREMENT INSTRUMENT IDENTIFICATION NUMBER DCA100-85-C-0010 | |
| 8c ADDRESS (City, State, and ZIP Code) Washington, D.C. 20305-2010 | | | 10 SOURCE OF FUNDING NUMBERS | | |
| PROGRAM ELEMENT NO 33127K | | PROJECT NO | | TASK NO D1.6 | WORK UNIT CRDI D008 |
| 11 TITLE (Include Security Classification) <i>Volume III</i> Electromagnetic Pulse Transient Threat Testing of Protection Devices for Amateur Military Affiliate Radio System Equipment (U) <i>Section 5, Equipment & Devices Oscilloscope Photographs</i> | | | | | |
| 12 PERSONAL AUTHOR(S) Dennis Bodson, NCS; Joseph Frizzell and Thomas Higdon (ESI); Walter Rabke (Consultant) | | | | | |
| 13a TYPE OF REPORT Technical | | 13b TIME COVERED FROM TO | | 14 DATE OF REPORT (Year, Month, Day) 1985, October, 31 | |
| 15 PAGE COUNT | | | | | |
| 16 SUPPLEMENTARY NOTATION | | | | | |
| 17 COSATI CODES | | | 18. SUBJECT TERMS (Continue on reverse if necessary and identify by block number) | | |
| FIELD | GROUP | SUB-GROUP | Amateur Radio Equipment EMP, Lightning Protection, Electro- magnetic Pulse (EMP) Protection Devices Test, EMP, Lightning, Transient Electrical Magnetic Pulses. | | |
| | | | | | |
| 19 ABSTRACT (Continue on reverse if necessary and identify by block number) | | | | | |
| <p>This technical report discusses the vulnerability of equipment used by amateur/MARS radio operators in the United States to disruption or damage by transient electromagnetic effects such as lightning, voltage surges, and electromagnetic pulse (EMP) waves. It also reports the results of two test programs; one to evaluate existing transient suppression devices and components, and one to evaluate the response of amateur radio equipment to an EMP transient environment.</p> <p>Based on the test results, the report recommends procedures and a low-cost installation scheme which will significantly increase the operational survivability of amateur type communications equipment in a lightning or EMP environment.</p> <p>This report consists of three volumes. Volume I (200 pages) contains the test results and recommendations for transient protection of amateur radio equipment. Volume II</p> | | | | | |
| 20 DISTRIBUTION/AVAILABILITY OF ABSTRACT UNCLASSIFIED/UNLIMITED <input type="checkbox"/> SAME AS RPT. <input type="checkbox"/> DTIC USERS | | | 21 ABSTRACT SECURITY CLASSIFICATION Unclassified | | |
| 22a NAME OF RESPONSIBLE INDIVIDUAL Dennis Bodson | | | 22b TELEPHONE (Include Area Code) (202) 692-2124 | | 22c OFFICE SYMBOL NCS/TS |

UNCLASSIFIED

Block 19 Continued - ABSTRACT

(136 pages) contains supporting documentation including: the test plans for the two EMF tests, descriptions/specifications of the tested transient suppression devices and the amateur radio equipment, and photographs of the test facilities and test set-ups. Volume III (1290 pages) contains the raw test data in the form of oscilloscope photographs attached to the test data sheets for both test programs, as well as, written test descriptions and bench check measurements from the equipment test program. For most purposes Volume I should provide sufficient information. Volume II would be required to obtain more detailed descriptions of the test programs and tested devices and equipment. Volume III would only be required if a separate analysis of the test data is being made.

UNCLASSIFIED

NCS TECHNICAL INFORMATION BULLETIN 85-10


ELECTROMAGNETIC PULSE/TRANSIENT THREAT TESTING OF PROTECTION
DEVICES FOR AMATEUR/MILITARY AFFILIATE RADIO SYSTEM EQUIPMENT

OCTOBER 1985

PROJECT OFFICER

DENNIS BODSON
Senior Electronics Engineer
Office of Technology
and Standards

: APPROVED FOR PUBLICATION:


for MARSHALL L. CAIN
Assistant Manager
Office of Technology
and Standards

FOREWORD

The National Communications System (NCS) is an organization of the Federal government whose membership is comprised of 22 Government entities. Its mission is to assist the President, National Security Council, Office of Science and Technology Policy, and Office of Management and Budget in:

- o The exercise of their wartime and non-wartime emergency functions, and their planning and oversight responsibilities.
- o The coordination of the planning for and provision of National Security/Emergency Preparedness communications for the Federal government under all circumstances including crisis or emergency.

In support of this mission the NCS has executed a Memorandum of Understanding with the American Radio Relay League. Its purpose is to establish a broad framework for a cooperative and close working relationship with volunteer radio amateurs for support of national emergency communications functions. It is intended through joint coordination and exercise of the resources of both organizations, to enhance the nation-wide posture of telecommunications readiness for any conceivable national emergency. This particular Technical Information Bulletin is one of a series aimed at developing an awareness in the radio amateur community of practical, low cost EMP protective procedures, devices, and equipment which may if utilized significantly enhance the probability of amateur radio resources escaping serious damage during emergency situations involving EMP events.

Comments, on this TIB are welcome, and should be addressed to:

Office of the Manager
National Communications System
ATTN: NCS-TS
Washington, DC 20305-2010
(202) 692-2124


| | | |
|---------------|---------------|----------|
| Date | 7-29-85 11:25 | |
| Test Point | TA. | |
| Amplification | dB | |
| Attenuation | dB | |
| Horizontal | 200 | ns/div 1 |
| Vertical | 200 | mV/div 1 |
| Horizontal | ns/div 2 | |
| Vertical | ns/div 2 | |
| Configuration | Pulse 1 | |
| Pulse Level | 25.3 KV | |
| Data Link | H-SENSOR | |

Comments:

200 mA/div

48.2 KV/m SYSTEMS 1, 4, 10, 14.

OUTPUT 820 mV.




| | | |
|---------------|--------------|----------|
| Date | 7-29-85/1500 | |
| Test Point | TB-L | |
| Amplification | dB | |
| Attenuation | dB | |
| Horizontal | 200 | ns/div 1 |
| Vertical | 200 | mV/div 1 |
| Horizontal | ns/div 2 | |
| Vertical | ns/div 2 | |
| Configuration | PULSE 2 | |
| Pulse Level | 25.3KV | |
| Data Link | H SENSOR | |

Comments:

200 mA/div

41.2 KV/m SYSTEMS 1, 4, 10


OUTPUT 700 mV



Date 7-29-85 / 1625
 Test Point TB-2 + TA
 Amplification dB
 Attenuation dB
 Horizontal 200 ns/div 1
 Vertical 200 mV/div 1
 Horizontal ns/div 2
 Vertical ns/div 2
 Configuration PULSE 3 KV
 Pulser Level 25.3 CHARGE
 Data Link H SENSOR

Comments:

780 mV output
 45.9 kV/m




TA = 6, 7, 8, 12 + 13
 TB-2 = 1+4

Date 7-30-85 / 1204
 Test Point TA-
 Amplification dB
 Attenuation dB
 Horizontal 200 ns/div 1
 Vertical 200 mV/div 1
 Horizontal ns/div 2
 Vertical ns/div 2
 Configuration PULSE 4
 Pulser Level 29 KV
 Data Link H SENSOR


Comments:

880 mV output
 51.8 kV/m -



TA = 2, 3, 5, 9, 11 + 16

| | |
|---------------|----------------|
| Date | 7-30-85 / 1523 |
| Test Point | TB |
| Amplification | dB |
| Attenuation | dB |
| Horizontal | ns/div 1 |
| Vertical | mV/div 1 |
| Horizontal | ns/div 2 |
| Vertical | ns/div 2 |
| Configuration | |
| Pulse Level | 29 KV - CHARGE |
| Data Link | |



Comments:

OUTPUT 850 MV →
50.0 KV/M

SYSTEMS - 2, 3, 5, 9, 11 + 16

| | |
|---------------|----------|
| Date | |
| Test Point | |
| Amplification | dB |
| Attenuation | dB |
| Horizontal | ns/div 1 |
| Vertical | mV/div 1 |
| Horizontal | ns/div 2 |
| Vertical | ns/div 2 |
| Configuration | |
| Pulse Level | |
| Data Link | |

Comments:

Date 7-31-85
 Test Point MOSLEY - 1
 Amplification dB
 Attenuation 40 dB
 Horizontal 200 ns/div 1
 Vertical 1 mV/div 1
 Horizontal ns/div 2
 Vertical ns/div 2
 Configuration
 Pulsar Level 20KV CHARGE
 Data Link


Comments:

- CURRENT FROM ANTENNA
- CURRENT THROUGH BOTH CENTER + SHIELD DIRECT TO GND 20KV CHARGE 91550-2 (1Ω) PROBE

1

MOSLEY TA33 JR ANTENNA - 8' FROM GRND - ANTENNA ELEMENTS WERE AT RIGHT ANGLE TO DRIVE LINE.

① 40dB, 1 V/div 200ns/div peak current 280 A (14KV)




Date 7-31-85
 Test Point MOSLEY - 2
 Amplification dB
 Attenuation 40 dB
 Horizontal 200 ns/div 1
 Vertical 0.5 mV/div 1
 Horizontal ns/div 2
 Vertical ns/div 2
 Configuration
 Pulsar Level 20KV charge
 Data Link

Comments:


peak current 260 A
 (13KV) 2

SET UP:

- MOSLEY TA 33 JR. ANTENNA 8' ABOVE GND.
- ANTENNA ELEMENTS AT RIGHT ANGLE TO PULSER DRIVE LINES
- CURRENT THROUGH BOTH CENTER + SHIELD DIRECT TO GND.
- 20 KV CHARGE • 91550-2 (1Ω) PROBE.




Date 7-31-85
 Test Point MOSLEY - 3
 Amplification dB
 Attenuation 40 dB
 Horizontal 100 ns/div 1
 Vertical 0.5 V/div 1
 Horizontal ns/div 2
 Vertical ns/div 2
 Configuration
 Pulsar Level 20KV CHARGE
 Data Link



Comments:
 PEAK CURRENT = 275 A
 (13.75KV) (3)

SET UP SAME AS MOSLEY 1 + 2.

Date 7-31-85
 Test Point MOSLEY - 4
 Amplification dB
 Attenuation 26 dB
 Horizontal 100 ns/div 1
 Vertical 1 V/div 1
 Horizontal ns/div 2
 Vertical ns/div 2
 Configuration
 Pulsar Level 20KV-CHARGE
 Data Link



Comments:
 PEAK CURRENT 106 53 A
 (5.4KV) (4)

SET UP: • GROUNDED SHIELD OF RG8 TO PLATE • CENTER WIRE OF RG-8 THROUGH CURRENT(I) PROBE TO GROUND THROUGH 51 OHM RESISTOR.

• 20 dB + 6 dB SMA - HEWETT PACKARD ATTENUATORS

Date 7-31-85

Test Point MOSLEY -5

Amplification dB

Attenuation 26 dB

Horizontal 100 ns/div 1

Vertical 1 μ V/div 1

Horizontal ns/div 2

Vertical ns/div 2

Configuration

Pulse Level 20 KV CHARGE

Data Link


Comments:

PEAK CURRENT +52A, -76A

(3.9KV)

(5)

SET UP: SAME AS MOSLEY 4



Date 7-31-85

Test Point MOSLEY -6

Amplification dB

Attenuation 26 dB

Horizontal 100 ns/div 1

Vertical 1 μ V/div 1

Horizontal ns/div 2

Vertical ns/div 2

Configuration

Pulse Level 20 KV CHARGE


Data Link

Comments:

PEAK CURRENT: OFF SCALE

(6)


SET UP: USING 50 OHM DUMMY LOAD "ANTENNA"
 GROUNDED. CURRENT THROUGH CENTER CONDUCTORS.
 • SHIELDS GROUNDED.



Date 7-31-85
 Test Point MOSLEY-7
 Amplification dB
 Attenuation 20 dB
 Horizontal 50 μ s/div 1
 Vertical 1 V/div 1
 Horizontal ns/div 2
 Vertical ns/div 2
 Configuration
 Pulsar Level 20 KV CHARGE.
 Data Link

Comments:

PEAK CURRENT 42 A
 (2.1 KV) (7)
 SET UP. SAME AS 6.




Date 7-31-85
 Test Point ~~MOSLEY-7~~ PROBE 1
 Amplification dB
 Attenuation dB
 Horizontal 200 ns/div 1
 Vertical 200 mV/div 1
 Horizontal ns/div 2
 Vertical ns/div 2
 Configuration
 Pulsar Level
 Data Link

Comments: PROBE CHECK 1

(8)


SET UP: REMOVED I PROBE - INSTALLED H PROBE

NOTE: CABLE GROUNDED - BREAKER TRIPPED.



| | |
|---------------|---------------|
| Date | 7-31-85 |
| Test Point | PROBE CHECK-9 |
| Amplification | dB |
| Attenuation | dB |
| Horizontal | 200 ns/div 1 |
| Vertical | 200 mV/div 1 |
| Horizontal | ns/div 2 |
| Vertical | ns/div 2 |
| Configuration | |
| Pulse Level | 20KV CHARGE |
| Data Link | |

Comments:




(9)

REPEAT 8 CABLE FROM ANTENNA
ISOLATED - POWER BREAKER
TRIPPED.

| | |
|---------------|-------------------|
| Date | 7-31-85 |
| Test Point | PROBE-CALIBRATION |
| Amplification | dB 10 |
| Attenuation | dB |
| Horizontal | 200 ns/div 1 |
| Vertical | 200 mV/div 1 |
| Horizontal | ns/div 2 |
| Vertical | ns/div 2 |
| Configuration | |
| Pulse Level | 20KV CHARGE |
| Data Link | |


Comments:



(10)


REPEAT 8+9 ANTENNA CABLE
TIED HIGH ON TO ANTENNA
POWER BREAKER DID NOT TRIP.

Date 7-31-85
 Test Point PROBE - CAL - 11
 Amplification dB
 Attenuation dB
 Horizontal 200 ns/div 1
 Vertical 200 mV/div 1
 Horizontal ns/div 2
 Vertical ns/div 2
 Configuration
 Pulsar Level 29 KV CHARGE
 Data Link
 Comments:




(11)
 SET UP: H FIELD SENSOR - ANTENNA REMOVED
~~MAN MAN MAN MAN~~

Date 7-31-85
 Test Point CALIBRATION 12
 Amplification dB
 Attenuation dB
 Horizontal 200 ns/div 1
 Vertical 200 mV/div 1
 Horizontal ns/div 2
 Vertical ns/div 2
 Configuration
 Pulsar Level 25 KV CHARGE
 Data Link
 Comments:



1000 mV → 58.8 KV / 12
~~MAN MAN MAN MAN~~ -


Date 7-31-85
 Test Point CAL - 13
 Amplification dB
 Attenuation dB
 Horizontal 200 ns/div 1
 Vertical 200 mV/div 1
 Horizontal ns/div 2
 Vertical ns/div 2
 Configuration
 Pulsar Level 25KV CHARGE
 Data Link



Comments:

~~1000mV~~ 1000mV → 58.8 KV/μs (13)

Date 7-31-85
 Test Point CAL - 14
 Amplification dB
 Attenuation dB
 Horizontal 200 ns/div 1
 Vertical 1 mV/div 1
 Horizontal ns/div 2
 Vertical ns/div 2
 Configuration
 Pulsar Level 25KV CHARGE
 Data Link



Comments:


→ 3V → 56.6 KV/μs (14)

RECTANGULAR H SENSOR

Date 7-31-85
 Test Point CAL-15
 Amplification dB
 Attenuation dB
 Horizontal 200 ns/div 1
 Vertical 200 mV/div 1
 Horizontal ns/div 2
 Vertical ns/div 2
 Configuration
 Pulsar Level 25KV CHARGE
 Data Link
 Comments:

> 880 mV → 57.6 kV/m (15)


~~DEPOSED DATA~~
 ROUND H SENSOR




Date 7-31-85
 Test Point CAL-16
 Amplification dB
 Attenuation dB
 Horizontal 200 ns/div 1
 Vertical 200 mV/div 1
 Horizontal ns/div 2
 Vertical ns/div 2
 Configuration
 Pulsar Level 22KV CHARGE
 Data Link
 Comments:

(16)

ROUND H SENSOR




| | |
|---------------|--------------|
| Date | 7-31-85 |
| Test Point | CAL - 17 |
| Amplification | dB |
| Attenuation | dB |
| Horizontal | 200 ns/div 1 |
| Vertical | 200 mV/div 1 |
| Horizontal | ns/div 2 |
| Vertical | ns/div 2 |
| Configuration | |
| Pulse Level | 22 KV CHARGE |
| Data Link | |
| Comments: | |



17

ROUND H SENSOR


| | |
|---------------|--------------|
| Date | 7-31-85 |
| Test Point | TB - |
| Amplification | dB |
| Attenuation | dB |
| Horizontal | 200 ns/div 1 |
| Vertical | 200 mV/div 1 |
| Horizontal | ns/div 2 |
| Vertical | ns/div 2 |
| Configuration | |
| Pulse Level | 22 KV CHARGE |
| Data Link | |
| Comments: | |



18

ROUND H SENSOR
EQUIP. IN FIELD
SYSTEM - 14

| | | |
|---------------|-------------|----------|
| Date | 7-31-85 | 1505 |
| Test Point | TCL | |
| Amplification | dB | |
| Attenuation | dB | |
| Horizontal | 200 | ns/div 1 |
| Vertical | 200 | mV/div 1 |
| Horizontal | | ns/div 2 |
| Vertical | | ns/div 2 |
| Configuration | | |
| Pulse Level | 22KV CHARGE | |
| Data Link | | |
| Comments: | | |




14/30PSI-~~WAVEN~~ -
H SENSOR

(19)

(SYSTEM 2) GROUNDED

| | |
|---------------|--------------|
| Date | 7-31-85 |
| Test Point | TC-2 |
| Amplification | dB |
| Attenuation | dB |
| Horizontal | 200 ns/div 1 |
| Vertical | 200 mV/div 1 |
| Horizontal | ns/div 2 |
| Vertical | ns/div 2 |
| Configuration | |
| Pulse Level | 22KV CHARGE |
| Data Link | |
| Comments: | |




~~WAVEN~~ -
H - SENSOR

(20)

(SYSTEM 2)

| | |
|---------------|---------------|
| Date | 7-31-85 |
| Test Point | TC-3 |
| Amplification | dB |
| Attenuation | dB |
| Horizontal | 200 ns/div 1 |
| Vertical | 200 mV/div 1 |
| Horizontal | ns/div 2 |
| Vertical | ns/div 2 |
| Configuration | |
| Pulse Level | 22KV -CHARGE |
| Data Link | |
| Comments: | |




~~XXXXXXXXXX~~

(21)

(SYSTEM 2) TC-3 (TEST)

| | |
|---------------|--------------|
| Date | 8-1-85 |
| Test Point | TC-4 |
| Amplification | dB |
| Attenuation | dB |
| Horizontal | 200 ns/div 1 |
| Vertical | 200 mV/div 1 |
| Horizontal | ns/div 2 |
| Vertical | ns/div 2 |
| Configuration | |
| Pulse Level | 22KV CHARGE |
| Data Link | |
| Comments: | |




(24)

(SYSTEM 2) TC4 TEST


Date August 1, 1985
 Test Point PULSER CAL
 Amplification dB
 Attenuation dB
 Horizontal 200 ns/div 1
 Vertical 200 mV/div 1
 Horizontal ns/div 2
 Vertical mV/div 2
 Configuration
 Pulsar Level 22KV Charge
 Data Link
 Comments:

(22)



Date August 1, 1985
 Test Point PULSER CAL
 Amplification dB
 Attenuation dB
 Horizontal 200 ns/div 1
 Vertical 200 mV/div 1
 Horizontal ns/div 2
 Vertical mV/div 2
 Configuration
 Pulsar Level 22KV Charge
 Data Link
 Comments:

(23)



4.3 div

Date August 1, 1985

Test Point

Amplification dB

Attenuation dB

Horizontal 200 ns/div 1

Vertical 200 mV/div 1

Horizontal 200 ns/div 2

Vertical 100 mV/div 2


Configuration

Pulse Level 22KV charge

Data Link

Comments:

(24)



Date August 1, 1985

Test Point

Amplification dB

Attenuation dB

Horizontal 200 ns/div 1

Vertical 200 mV/div 1

Horizontal ns/div 2

Vertical mV/div 2


Configuration

Pulse Level 22KV charge

Data Link


Comments:

(25)



NO OSC - NORMAL COND .


| | | | |
|---------------|----------------|---|--|
| Date | August 1, 1985 | | |
| Test Point | | | |
| Amplification | dB | | |
| Attenuation | dB | | |
| Horizontal | 200 ns/div | 1 | |
| Vertical | 200 mV/div | 1 | |
| Horizontal | ns/div | 2 | |
| Vertical | mV/div | 2 | |
| Configuration | | | |
| Pulse Level | 22KV Charge | | |
| Data Link | | | |
| Comments: | | | |



(26)

CORD STRETCHED TOWARD GEN

| | | | |
|---------------|----------------|---|--|
| Date | August 1, 1985 | | |
| Test Point | GENERATOR TEST | | |
| Amplification | dB | | |
| Attenuation | dB | | |
| Horizontal | 200 ns/div | 1 | |
| Vertical | 200 mV/div | 1 | |
| Horizontal | ns/div | 2 | |
| Vertical | mV/div | 2 | |
| Configuration | | | |
| Pulse Level | 22KV Charge | | |
| Data Link | | | |
| Comments: | | | |




(27)

GEN ON - CONNECTED.

Date August 1, 1985
 Test Point PULSER CAL
 Amplification dB
 Attenuation dB
 Horizontal 200 ns/div 1
 Vertical 200 mV/div 1
 Horizontal ns/div 2
 Vertical mV/div 2
 Configuration
 Pulsor Level 22KV charge
 Data Link
 Comments:


(28)



2 LOAD RESISTORS REMOVED
 FROM PULSER -


Date August 1, 1985
 Test Point PULSER CA
 Amplification dB
 Attenuation dB
 Horizontal 200 ns/div 1
 Vertical 200 mV/div 1
 Horizontal ns/div 2
 Vertical mV/div 2
 Configuration
 Pulsor Level 22KV charge
 Data Link
 Comments:

(29)



CAP. CLOSED 5 TURNS


Date 8-1-85 / 1106
 Test Point WIRE ANTENNA
 Amplification dB
 Attenuation 26 dB
 Horizontal 200 ns/div 1
 Vertical 1 mV/div 1
 Horizontal ns/div 2
 Vertical ns/div 2
 Configuration
 Pulsar Level 22 KV - CHARGE
 Data Link
 Comments:



(30)

50 Ω LOAD TO GROUND
 WIRE ANTENNA (SHORT VERTICAL)
 FIRST SPIKE - 70 AMPS - (3.5 KV/)
 LARGE SPIKE - 80 AMPS - (4.0 KV/)

Date 8-1-85 / 1155
 Test Point WIRE ANTENNA
 Amplification dB
 Attenuation 46 dB
 Horizontal 200 ns/div 1
 Vertical 200 mV/div 1
 Horizontal ns/div 2
 Vertical ns/div 2
 Configuration
 Pulsar Level 22 KV CHARGE
 Data Link
 Comments:



(31)

ANTENNA - SHORT VERTICAL + LONG HORIZONTAL
 50 Ω LOAD TO GROUND

SPIKE - 220 AMPS \rightarrow (11 KV/)

5.5 div \times 200 = 1.1 volts \times 200 = 220 A \times 50 Ω = 11,000 V

Date 8-1-85
 Test Point POWER INJECT PULSE
 Amplification dB
 Attenuation 46 dB
 Horizontal 200 ns/div 1
 Vertical 100 mV/div 1
 Horizontal ns/div 2
 Vertical ns/div 2
 Configuration
 Pulser Level 22KV-
 Data Link
 Comments:


110 A

(31)

SHORT WIRE ANTENNA PULSE -

SPIKE - 5.5 KV/


ANTENNA SHORTENED AND
 ON SIDE OF PULSER




Date 8-1-85
 Test Point POWER - PROBE -
 Amplification dB
 Attenuation 46 dB
 Horizontal 200 ns/div 1
 Vertical 100 mV/div 1
 Horizontal ns/div 2
 Vertical ns/div 2
 Configuration
 Pulser Level 22KV
 Data Link
 Comments:

(32)

PROBE CALIBRATION (~~WIRE~~) USED FOR SHORT
 WIRE ANTENNA MEASUREMENT ABOVE -




Date 8-1-85 / 1426
 Test Point CUSHCRAFT AV-5
 Amplification dB
 Attenuation 46 dB
 Horizontal 200 ns/div 1
 Vertical 1 mV/div 1
 Horizontal ns/div 2
 Vertical ns/div 2
 Configuration
 Pulsar Level 22KV CHARGE
 Data Link
 Comments:



33

CUSHCRAFT AV-5 CONNECTED TO (46dB 0.2V)
 ANTENNA (dummy load) singer Probe -
 $160 A \times 50 \Omega = 8 KV$


Date 8-1-85 - 1430
 Test Point CUSHCRAFT AV-5
 Amplification dB
 Attenuation 40 dB
 Horizontal 100 ns/div 1
 Vertical 500 mV/div 1
 Horizontal ns/div 2
 Vertical ns/div 2
 Configuration
 Pulsar Level 22KV CHARGE
 Data Link
 Comments:



34


130 A (6.5KV)

Date August 1, 85
 Test Point CUSH CRAFT
 Amplification dB
 Attenuation dB
 Horizontal 100 ns/div 1
 Vertical 200 mV/div 1
 Horizontal ns/div 2
 Vertical mV/div 2
 Configuration
 Pulse Level 22 kV Charge
 Data Link
 Comments:



(34)

Date August 1, 85
 Test Point CUSH CRAFT
 Amplification dB
 Attenuation 40 dB
 Horizontal 100 ns/div 1
 Vertical 500 mV/div 1
 Horizontal ns/div 2
 Vertical mV/div 2
 Configuration
 Pulse Level 22 kV Charge
 Data Link
 Comments:




(35)

REPEAT - 34

150A (7.5KV)

| | |
|---------------|----------------|
| Date | August 1, 1985 |
| Test Point | CUSH CRAFT |
| Amplification | dB |
| Attenuation | 40 dB |
| Horizontal | 100 ns/div 1 |
| Vertical | 500 mV/div 1 |
| Horizontal | ns/div 2 |
| Vertical | mV/div 2 |
| Configuration | |
| Pulse Level | 22KV Charge |
| Data Link | |
| Comments: | |




(36)

CUSH CRAFT/ANTENNA 40dB 0.5

-145 A (7.25 KV)


| | |
|---------------|----------------|
| Date | August 1, 1985 |
| Test Point | CUSH CRAFT |
| Amplification | dB |
| Attenuation | 40 dB |
| Horizontal | 100 ns/div 1 |
| Vertical | 500 mV/div 1 |
| Horizontal | ns/div 2 |
| Vertical | mV/div 2 |
| Configuration | |
| Pulse Level | 22KV Charge |
| Data Link | |
| Comments: | |



(37)


REMOVED EXTRA COPPER WIRE
N - 150 A (7.5 KV)

| | |
|---------------|---------------------|
| Date | 8-1-85 |
| Test Point | CUSHCRAFT AV-5 |
| Amplification | dB |
| Attenuation | 40 dB |
| Horizontal | 100 ns/div 1 |
| Vertical | 500 mV/div 1 |
| Horizontal | ns/div 2 |
| Vertical | ns/div 2 |
| Configuration | |
| Pulse Level | 22 22 KV |
| Data Link | |
| Comments: | |



38
 REPLACED ANTENNA (DUMMY LOAD) WITH 50- Ω RESISTOR.
 150A (2.5KV)

| | |
|---------------|----------|
| Date | |
| Test Point | |
| Amplification | dB |
| Attenuation | dB |
| Horizontal | ns/div 1 |
| Vertical | mV/div 1 |
| Horizontal | ns/div 2 |
| Vertical | ns/div 2 |
| Configuration | |
| Pulse Level | |
| Data Link | |
| Comments: | |



Date August 1, 1985

Test Point

Amplification dB

Attenuation dB

Horizontal 100 ns/div 1

Vertical 100 mV/div 1

Horizontal ns/div 2


Vertical mV/div 2

Configuration

Pulse Level 22 KV Charge

Data Link

Comments:



(39)

60dB FIBER OPTIC COUPLING

Date August 1, 1985

Test Point

Amplification dB

Attenuation dB

Horizontal 200 ns/div 1

Vertical 500 mV/div 1

Horizontal 200 ns/div 2


Vertical 100 mV/div 2

Configuration

Pulse Level 22 KV Charge


Data Link

Comments:



(40)


Date August 1, 1985
 Test Point
 Amplification dB
 Attenuation dB
 Horizontal 200 ns/div 1
 Vertical 500 mV/div 1
 Horizontal 200 ns/div 2
 Vertical 200 mV/div 2
 Configuration
 Pulse Level 22KV Charge
 Data Link
 Comments:



(41)

LOWER TRACE : FO.
 UPPER TRACE : ANTENNA SIGNAL

Date August 1, 1985
 Test Point
 Amplification dB
 Attenuation dB
 Horizontal 200 ns/div 1
 Vertical 500 mV/div 1
 Horizontal 200 ns/div 2
 Vertical 200 mV/div 2
 Configuration
 Pulse Level 22KV Charge
 Data Link
 Comments:



(42)

REPEAT

Date August 1, 1985

Test Point

Amplification dB

Attenuation dB

Horizontal 100 ns/div 1

Vertical 500 mV/div 1

Horizontal 100 ns/div 2


Vertical 100 mV/div 2

Configuration

Pulse Level 22 KV Charge

Date Link

Comments:



(43)

REPEAT

Date August 1, 1985

Test Point

Amplification dB

Attenuation dB

Horizontal 100 ns/div 1

Vertical 200 mV/div 1

Horizontal 100 ns/div 2


Vertical 500 mV/div 2

Configuration

Pulse Level 22 KV Charge

Date Link


Comments:



(44)

LOWER TRACE - ROUND H SENSOR DIRECT 200 MV
 UPPER - RECTANGULAR H SENSOR - 500 MV


| | |
|---------------|----------------|
| Date | August 2, 1985 |
| Test Point | PULSER CAL |
| Amplification | dB |
| Attenuation | dB |
| Horizontal | 100 ns/div 1 |
| Vertical | 200 mV/div 1 |
| Horizontal | ns/div 2 |
| Vertical | mV/div 2 |
| Configuration | |
| Pulser Level | 28KV Charge |
| Data Link | |
| Comments: | |



①


H SENSUR ~ 5 FT FROM FRONT

| | |
|---------------|----------------|
| Date | August 2, 1985 |
| Test Point | PULSER CAL |
| Amplification | dB |
| Attenuation | dB |
| Horizontal | 100 ns/div 1 |
| Vertical | 200 mV/div 1 |
| Horizontal | ns/div 2 |
| Vertical | mV/div 2 |
| Configuration | |
| Pulser Level | 30KV Charge |
| Data Link | |
| Comments: | |



②


Date August 2, 1985
 Test Point PULSER CAL
 Amplification dB
 Attenuation dB
 Horizontal 200 ns/div 1
 Vertical 200 mV/div 1
 Horizontal ns/div 2
 Vertical mV/div 2
 Configuration
 Pulsar Level 30 KV charge
 Data Link
 Comments:



(3)

REPEAT 2


Date August 2, 1985
 Test Point PULSER CAL
 Amplification dB
 Attenuation dB
 Horizontal 200 ns/div 1
 Vertical 500 mV/div 1
 Horizontal 200 ns/div 2
 Vertical 200 mV/div 2
 Configuration
 Pulsar Level 30 KV charge
 Data Link
 Comments:



(4)

UPPER - F.O. (GAIN $\frac{76}{43}$) 60dB 200mV
 LOWER: ROUND H SENSOR 500 mV


| | | | |
|---------------|----------------|---|--|
| Date | August 2, 1985 | | |
| Test Point | | | |
| Amplification | dB | | |
| Attenuation | dB | | |
| Horizontal | 200 ns/div | 1 | |
| Vertical | 500 mV/div | 1 | |
| Horizontal | 200 ns/div | 2 | |
| Vertical | 100 mV/div | 2 | |
| Configuration | | | |
| Pulse Level | 30KV Charge | | |
| Data Link | | | |
| Comments: | | | |



(5)

REPEAT (4) 40dB FO. 100mV

| | | | |
|---------------|----------------|---|--|
| Date | August 2, 1985 | | |
| Test Point | CUSHCRAFT | | |
| Amplification | dB | | |
| Attenuation | dB | | |
| Horizontal | 200 ns/div | 1 | |
| Vertical | 500 mV/div | 1 | |
| Horizontal | 200 ns/div | 2 | |
| Vertical | 200 mV/div | 2 | |
| Configuration | | | |
| Pulse Level | 30KV Charge | | |
| Data Link | | | |
| Comments: | | | |




(6)

UPPER: FO. 6dB FO GAIN 1.0
 LOWER: DIRECT TO ANTENNA 20dB

off scale

| | |
|---------------|----------------|
| Date | August 2, 1985 |
| Test Point | CN54CRAFT |
| Amplification | dB |
| Attenuation | dB |
| Horizontal | 200ns/div 1 |
| Vertical | 500 mV/div 1 |
| Horizontal | 200ns/div 2 |
| Vertical | 200mV/div 2 |
| Configuration | |
| Pulse Level | 30KV Charge |
| Data Link | |
| Comments: | |



⑦


UPPER: ANTENNA 20dB

LOWER: F.D. FIELD - 6dB


off scale

| | |
|---------------|----------|
| Date | |
| Test Point | |
| Amplification | dB |
| Attenuation | dB |
| Horizontal | ns/div 1 |
| Vertical | mV/div 1 |
| Horizontal | ns/div 2 |
| Vertical | mV/div 2 |
| Configuration | |
| Pulse Level | |
| Data Link | |
| Comments: | |


| | | |
|---------------|------------------------|----------|
| Date | August 2, 1985 | |
| Test Point | ANTENNA | |
| Amplification | dB | |
| Attenuation | 20 | dB |
| Horizontal | 200 | ns/div 1 |
| Vertical | 500 | mV/div 1 |
| Horizontal | ns/div 2 | |
| Vertical | mV/div 2 | |
| Configuration | | |
| Pulse Level | 30KV charge | |
| Data Link | | |
| Comments: | CUSHCRAFT off scale | |



| | | |
|---------------|------------------------|----------|
| Date | August 2, 1985 | |
| Test Point | ANTENNA - | |
| Amplification | dB | |
| Attenuation | 20 | dB |
| Horizontal | 200 | ns/div 1 |
| Vertical | 1000 | mV/div 1 |
| Horizontal | ns/div 2 | |
| Vertical | mV/div 2 | |
| Configuration | | |
| Pulse Level | 30KV charge | |
| Data Link | | |
| Comments: | CUSHCRAFT off scale | |



Date August 2, 1985
 Test Point CWSH CRAFT
 Amplification dB
 Attenuation 40 dB
 Horizontal 200 ns/div 1
 Vertical 1000 mV/div 1
 Horizontal ns/div 2
 Vertical mV/div 2
 Configuration
 Pulse Level 30 KV charge
 Data Link
 Comments:




(11)

~~40~~ 20 dB IN LINE

off scale


Date August 2, 1985
 Test Point CWSH CRAFT
 Amplification dB
 Attenuation 40 dB
 Horizontal 200 ns/div 1
 Vertical 200 mV/div 1
 Horizontal ns/div 2
 Vertical mV/div 2
 Configuration
 Pulse Level 30 KV charge
 Data Link
 Comments:



(12)

40dB in LINE ANTENNA TRALE ONLY -
 SPIKE +110A - (5.5 KV)

Date August 2, 1985
 Test Point CUSHERAET
 Amplification dB
 Attenuation dB
 Horizontal 200 ns/div 1
 Vertical 200 mV/div 1
 Horizontal ns/div 2
 Vertical mV/div 2
 Configuration
 Pulsar Level 30KV/charge
 Data Link
 Comments:




(13)

SENSOR CT2 SIGNAL OFF SCALE


Date
 Test Point
 Amplification dB
 Attenuation dB
 Horizontal ns/div 1
 Vertical mV/div 1
 Horizontal ns/div 2
 Vertical mV/div 2
 Configuration
 Pulsar Level
 Data Link
 Comments:

Date 8-2-85
 Test Point POWER INJECT
 Amplification dB
 Attenuation 40 dB
 Horizontal 200 ns/div 1
 Vertical 500 mV/div 1
 Horizontal ns/div 2
 Vertical ns/div 2
 Configuration
 Pulse Level 30 KV CHARGE
 Data Link
 Comments: 6.4KV
 ~ 170 A (8.5KV) 15



VERTICAL "L" SHAPED FIELD WIRE - 50 OHMS
 TO GROUND
 PRELIMINARY POWER INJECT
~~APR 22 1985~~

Date 8-2-85
 Test Point CUSHCRAFT AV-5
 Amplification dB
 Attenuation 40 dB
 Horizontal 200 ns/div 1
 Vertical 500 mV/div 1
 Horizontal ns/div 2
 Vertical ns/div 2
 Configuration
 Pulse Level 30 KV CHARGE
 Data Link
 Comments: 150 A (7.5KV)
 14




CUSHCRAFT AV-5 ANTENNA WITH RG-8 COAXIAL
 LINE 1 1/2 FOOT ABOVE FLOOR - SMALL CT.

| | |
|---------------|----------------|
| Date | 8-2-85 |
| Test Point | CUSHCRAFT AV-5 |
| Amplification | dB |
| Attenuation | dB |
| Horizontal | 200 ns/div 1 |
| Vertical | 500 mV/div 1 |
| Horizontal | ns/div 2 |
| Vertical | ns/div 2 |
| Configuration | |
| Pulse Level | 30 KV CHARGE |
| Data Link | |

Comments:

PEAK I = 170 A (8.67KV)
16

SET UP: CUSHCRAFT AV-5 DIAGONAL TO PULSE FIELD. 75' RG-8 COAXIAL CABLE AT ABOUT 8' (FOOT) HIGH LEVEL. 51Ω LOAD ON CENTER CONDUCTOR TO GROUND. CABLE SHIELD GROUNDED.
• SMALL CT USED. 50Ω LOAD TO GND




| | |
|---------------|---------------|
| Date | 8-2-85 |
| Test Point | COAXIAL CABLE |
| Amplification | dB |
| Attenuation | 40 dB |
| Horizontal | 200 ns/div 1 |
| Vertical | 500 mV/div 1 |
| Horizontal | ns/div 2 |
| Vertical | ns/div 2 |
| Configuration | |
| Pulse Level | 30KV CHARGE |
| Data Link | |

Comments:


COAXIAL CABLE TEST 18

SET UP: ANTENNA DISCONNECTED-

COAXIAL CABLE RG-8 8' FOOT ABOVE FLOOR. CABLE SHIELD GROUNDED AT BOTH ENDS. SIGNAL FROM CENTER CONDUCTOR.
51Ω LOAD TO GROUND. SENSOR 91550



| | | | |
|---------------|----------------|--------|---|
| Date | August 2, 1985 | | |
| Test Point | CNSHCRART | | |
| Amplification | dB | | |
| Attenuation | dB | | |
| Horizontal | 200 | ns/div | 1 |
| Vertical | 500 | mV/div | 1 |
| Horizontal | | ns/div | 2 |
| Vertical | | mV/div | 2 |
| Configuration | | | |
| Pulse Level | 30KV Charge | | |
| Date Link | | | |
| Comments: | | | |




(17)

REPEAT (16) SENSOR 91550 ~ 125A (6.375KV)

| | | | |
|---------------|----|--------|---|
| Date | | | |
| Test Point | | | |
| Amplification | dB | | |
| Attenuation | dB | | |
| Horizontal | | ns/div | 1 |
| Vertical | | mV/div | 1 |
| Horizontal | | ns/div | 2 |
| Vertical | | mV/div | 2 |
| Configuration | | | |
| Pulse Level | | | |
| Date Link | | | |
| Comments: | | | |


| | | | |
|---------------|----------------|--------|---|
| Date | August 2, 1985 | | |
| Test Point | RG8 CABLE | | |
| Amplification | dB | | |
| Attenuation | 40 | dB | |
| Horizontal | 200 | ns/div | 1 |
| Vertical | 20 | mV/div | 1 |
| Horizontal | ns/div | 2 | |
| Vertical | mV/div | 2 | |
| Configuration | | | |
| Pulse Level | 30KV Charge | | |
| Data Link | | | |
| Comments: | | | |



(19)

REPEAT 15 - AT 20 MV - NO SPIKE NOISE ONLY


| | | | |
|---------------|----------------|--------|---|
| Date | August 2, 1985 | | |
| Test Point | WIRE ANTENNA | | |
| Amplification | dB | | |
| Attenuation | 40 | dB | |
| Horizontal | 200 | ns/div | 1 |
| Vertical | 1000 | mV/div | 1 |
| Horizontal | ns/div | 2 | |
| Vertical | mV/div | 2 | |
| Configuration | | | |
| Pulse Level | 30KV Charge | | |
| Data Link | | | |
| Comments: | | | |



(20)

WIRE ANTENNA 50 OHMS TO GROUND - PULSE 91550
 40 dB 100 A/div 230 A PEAK. (11.5 KV)

| | |
|---------------|----------------|
| Date | August 2, 1985 |
| Test Point | WIRE ANTENNA |
| Amplification | dB |
| Attenuation | dB |
| Horizontal | 200 ns/div 1 |
| Vertical | 1000 mV/div 1 |
| Horizontal | 200 ns/div 2 |
| Vertical | 200 mV/div 2 |
| Configuration | |
| Pulse Level | 30KV Charge |
| Data Link | |
| Comments: | |




(23)

UPPER: WIRE ANTENNA 50 OHMS TO GROUND - PROBE 91550
 40 dB 100A/div 230 A PEAK - (11.5 KV)
 LOWER - F.O. TO H FIELD - FIELD $360 \text{ mV} \times 2 = 720 \text{ mV}$
 $17 \text{ mV/KV/m} = 42.3 \text{ KV/m}$

| | |
|---------------|----------|
| Date | |
| Test Point | |
| Amplification | dB |
| Attenuation | dB |
| Horizontal | ns/div 1 |
| Vertical | mV/div 1 |
| Horizontal | ns/div 2 |
| Vertical | mV/div 2 |
| Configuration | |
| Pulse Level | |
| Data Link | |
| Comments: | |

| | |
|---------------|--------------|
| Date | 8-2-85 |
| Test Point | CALIBRATION |
| Amplification | dB |
| Attenuation | dB |
| Horizontal | 200 ns/div 1 |
| Vertical | 200 mV/div 1 |
| Horizontal | 200 ns/div 2 |
| Vertical | 200 mV/div 2 |
| Configuration | |
| Pulse Level | 30 KV CHARGE |
| Data Link | |
| Comments: | |




26

LOWER TRACE - RECTANGULAR SENSOR 20 dB ATTN/
 $2.8 \text{ DIV} (280 \text{ mV} \times 10 \times 1.1 \div 20 = 154 \text{ A/m} \rightarrow 58 \text{ KV/M}$
 UPPER TRACE - ROUND H SENSOR - DIRECT
 $4.1 \text{ div} \times 200 \text{ mV} = 820 \text{ m} \rightarrow 48.2 \text{ KV/M}$

| | |
|---------------|----------|
| Date | |
| Test Point | |
| Amplification | dB |
| Attenuation | dB |
| Horizontal | ns/div 1 |
| Vertical | mV/div 1 |
| Horizontal | ns/div 2 |
| Vertical | ns/div 2 |
| Configuration | |
| Pulse Level | |
| Data Link | |
| Comments: | |

R F. DRIVE - REFERENCE

Date 8-2-85
 Test Point RF DRIVE -
 Amplification dB
 Attenuation 40 dB
 Horizontal 200 ns/div 1
 Vertical 1000 mV/div 1
 Horizontal 200 ns/div 2
 Vertical 200 mV/div 2
 Configuration
 Pulsar Level 30KV - DRIVE
 Data Link



Comments:

LONG L SHAPED WIRE
 VERTICAL +74" HIGH 28
 90° TO PULSER ELEMENTS.

UPPER TRACE - CURRENT - RF DRIVE - (91550 SENSOR)


$$350 \text{ A} \times 50 \Omega = 17,500 \text{ V}$$

LOWER TRACE - REFERENCE - H FIELD -

$$\sim 50 \text{ KV/m}$$

1" WIRE = 74" HIGH X 15' (FEET) LONG.

Date 8-2-85
 Test Point A.C. DRIVE (1)
 Amplification dB
 Attenuation 40 dB
 Horizontal 200 ns/div 1
 Vertical 1000 mV/div 1
 Horizontal 200 ns/div 2
 Vertical 200 mV/div 2
 Configuration
 Pulsar Level 30 KV -
 Data Link




Comments:

UPPER TRACE - ²⁹CURRENT - A.C. DRIVE - PRELIMINARY TEST

LOWER TRACE - REFERENCE - H FIELD - $\sim 50 \text{ KV/m}$

REFERENCE AC DRIVE

| | |
|---------------|----------------|
| Date | 8-2-85 |
| Test Point | A.C. DRIVE - R |
| Amplification | dB |
| Attenuation | 40 dB |
| Horizontal | 200 ns/div 1 |
| Vertical | 1000 mV/div 1 |
| Horizontal | 200 ns/div 2 |
| Vertical | 200 mV/div 2 |
| Configuration | |
| Pulse Level | 30KV DRIVE |
| Data Link | |



Comments:

SHORT "L" SHAPE WIRE
 55" VERTICAL + 72" HORIZ 30
 PARALLEL TO ELEMENTS OF PULSE

UPPER TRACE = A.C. DRIVE - $\frac{130 A}{\text{m}} \times 50 \text{ m} = 6500 \text{ V/m}$

LOWER TRACE = REF PULSE - $\sim 50 \text{ KV/m}$

55" x 72"


| | |
|---------------|----------|
| Date | |
| Test Point | |
| Amplification | dB |
| Attenuation | dB |
| Horizontal | ns/div 1 |
| Vertical | mV/div 1 |
| Horizontal | ns/div 2 |
| Vertical | ns/div 2 |
| Configuration | |
| Pulse Level | |
| Data Link | |
| Comments: | |

Date **8-2-85**
 Test Point **D-L**
 Amplification **dB**
 Attenuation **40 dB**
 Horizontal **200 ns/div 1**
 Vertical **1V mV/div 1**
 Horizontal **200 ns/div 2**
 Vertical **200MV ns/div 2**
 Configuration
 Pulsar Level **30KV CHARGE**
 Data Link **FIBER OPTIC + COAX**

Comments:

SYSTEM - 2


31



UPPER TRACE: AC ANTENNA CONNECTED TO "HOT" AC WIRE IN
 DUPLEX BOX. SINGER 915502 PROBE AROUND AC ANTENNA
 ABOVE BOX. $\pm 1/20 - 13A$, 25WATT LIGHT BULB CONNECTED AS LOAD
 HONDA GENERATOR THROUGH LONG CABLES + ISOLATION TRANSFORMER.
 LOWER TRACE: REF PULSE $\sim 50KV/\mu$ (130A (6.5KV))

Date
 Test Point
 Amplification **dB**
 Attenuation **dB**
 Horizontal **ns/div 1**
 Vertical **mV/div 1**
 Horizontal **ns/div 2**
 Vertical **ns/div 2**
 Configuration
 Pulsar Level
 Data Link
 Comments:

Date 8-2-85
 Test Point D-1
 Amplification dB
 Attenuation 20 dB
 Horizontal 200 ns/div 1
 Vertical 200 mV/div 1
 Horizontal ns/div 2
 Vertical ns/div 2
 Configuration
 Pulsar Level 30KV-CHARGE
 Data Link FIBER OPTICS
 Comments:



SYSTEM - 2 32

DRIVE - ANT + AC POWER

DEVICES - 3 , 39

~ 50KV/M

Date 8-2-85
 Test Point D-2
 Amplification dB
 Attenuation dB
 Horizontal ns/div 1
 Vertical mV/div 1
 Horizontal ns/div 2
 Vertical ns/div 2
 Configuration
 Pulsar Level
 Data Link
 Comments:

NO PHOTO

SYSTEM L

33


SAME AS (32)

Date 8-2-85
 Test Point D-3
 Amplification dB
 Attenuation 20 dB
 Horizontal ns/div 1
 Vertical mV/div 1
 Horizontal 200 ns/div 2
 Vertical 200 MV ns/div 2
 Configuration
 Pulsar Level 30KV CHARGE
 Data Link FIBER OPTICS
 Comments:

SYSTEM-4

35

$\sim 50 \text{ KV/m}$



Date 8-2-85
 Test Point
 Amplification dB
 Attenuation dB
 Horizontal ns/div 1
 Vertical mV/div 1
 Horizontal ns/div 2
 Vertical ns/div 2
 Configuration
 Pulsar Level
 Data Link

Comments:

SYSTEM 4

34

NO PHOTO

Date 8-2-85
 Test Point D-4 (1)
 Amplification dB
 Attenuation 20 dB
 Horizontal 200 ns/div 1
 Vertical 200 mV/div 1
 Horizontal ns/div 2
 Vertical ns/div 2
 Configuration
 Pulsar Level 30KV CHARGE
 Data Link


Comments:

SYSTEM-5

36

DOUBLE TRACE

50 KV/M



Date 8-2-85
 Test Point D-4 (2)
 Amplification dB
 Attenuation 20 dB
 Horizontal ns/div 1
 Vertical mV/div 1
 Horizontal 200 ns/div 2
 Vertical 200 mV/div 2
 Configuration
 Pulsar Level 30KV-CHARGE
 Data Link


Comments:

SYSTEM-5


37

DOUBLE TRACE

50 KV/M




Date 8-5-85
 Test Point CALIBRATION
 Amplification dB
 Attenuation dB
 Horizontal 200 ns/div 1
 Vertical 200 mV/div 1
 Horizontal 200 ns/div 2
 Vertical 200 mV/div 2
 Configuration
 Pulsar Level 30KV CHARGE
 Data Link
 Comments:




- 1
 1. LOWER TRACE: RECTANGULAR SENSOR -20dB INTO FIBER OPTIC
 2 UPPER TRACE: ROUND "H" SENSOR DIRECT NO ATTN.

Date 8-5-85
 Test Point TEST D-5
 Amplification dB
 Attenuation dB
 Horizontal ns/div 1
 Vertical mV/div 1
 Horizontal ns/div 2
 Vertical ns/div 2
 Configuration
 Pulsar Level
 Data Link
 Comments:



SYSTEM 10
DEVICES: 5A + 39 2
(TRACES
SAME AS PHOTO 1

| | | | |
|---------------|-------------|--------|---|
| Date | 8-5-85 | | |
| Test Point | TEST-D6 | | |
| Amplification | dB | | |
| Attenuation | dB | | |
| Horizontal | 200 | ns/div | 1 |
| Vertical | 200 | mV/div | 1 |
| Horizontal | 200 | ns/div | 2 |
| Vertical | 200 | mV/div | 2 |
| Configuration | | | |
| Pulse Level | 30KV CHARGE | | |
| Data Link | | | |



Comments:


SYSTEM - 11

DEVICES: 5A + 39 3

~ 50KV/M

TRACES SAME AS PHOTO 1 - 8-5-85

| | | | |
|---------------|-------------|--------|---|
| Date | 8-5-85 | | |
| Test Point | TEST-D7 | | |
| Amplification | dB | | |
| Attenuation | dB | | |
| Horizontal | 200 | ns/div | 1 |
| Vertical | 200 | mV/div | 1 |
| Horizontal | 200 | ns/div | 2 |
| Vertical | 200mV | mV/div | 2 |
| Configuration | | | |
| Pulse Level | 30KV CHARGE | | |
| Data Link | | | |



Comments:


SYSTEM - 16

DEVICES - 4B + 39 4

~ 50KV/M

TRACES SAME AS PHOTO 1 8-5-85

| | | | |
|---------------|-------------|--------|---|
| Date | 8-5-85 | | |
| Test Point | TEST D-8 | | |
| Amplification | dB | | |
| Attenuation | dB | | |
| Horizontal | 200 | ns/div | 1 |
| Vertical | 200 | mV/div | 1 |
| Horizontal | 200 | ns/div | 2 |
| Vertical | 200 MV | ns/div | 2 |
| Configuration | | | |
| Pulse Level | 30KV CHARGE | | |
| Data Link | | | |



Comments:

SYSTEM-3

DEVICES: 7 + 39 5


TRACES SAME AS PHOTO 1 8-5-85

~50 KV/m

| | | | |
|---------------|--------|---|--|
| Date | | | |
| Test Point | | | |
| Amplification | dB | | |
| Attenuation | dB | | |
| Horizontal | ns/div | 1 | |
| Vertical | mV/div | 1 | |
| Horizontal | ns/div | 2 | |
| Vertical | ns/div | 2 | |
| Configuration | | | |
| Pulse Level | | | |
| Data Link | | | |

Comments:


| | | |
|---------------|---------------|----------|
| Date | 8-5-85 - 1312 | |
| Test Point | TEST D9 | |
| Amplification | dB | |
| Attenuation | dB | |
| Horizontal | 200 | ns/div 1 |
| Vertical | 200 | mV/div 1 |
| Horizontal | 200 | ns/div 2 |
| Vertical | 200 mV | mV/div 2 |
| Configuration | | |
| Pulse Level | 30 KV Charge | |
| Data Link | | |
| Comments: | (SYSTEM 8) | |



6

UPPER - H FIELD DIRECT
 LOWER - RECTANGULAR PROBE - FIBER OPTIC
 ~ 50KV/M-

| | | |
|---------------|--------------|----------|
| Date | 8-5-85 | |
| Test Point | TEST D10 | |
| Amplification | dB | |
| Attenuation | dB | |
| Horizontal | 200 | ns/div 1 |
| Vertical | 200 | mV/div 1 |
| Horizontal | 200 | ns/div 2 |
| Vertical | 200 mV | mV/div 2 |
| Configuration | | |
| Pulse Level | 30 KV CHARGE | |
| Data Link | | |
| Comments: | (SYSTEM 9) | |




7

| | |
|---------------|--------------|
| Date | 8-5-85 |
| Test Point | TEST D-11 |
| Amplification | dB |
| Attenuation | dB |
| Horizontal | 200 ns/div 1 |
| Vertical | 200 mV/div 1 |
| Horizontal | 200 ns/div 2 |
| Vertical | 200 mV/div 2 |
| Configuration | |
| Pulse Level | 30KV CHARGE |
| Data Link | |

Comments:

(SYSTEM 6)

8




| | |
|---------------|--------------|
| Date | 8-5-85 |
| Test Point | TEST D-12 |
| Amplification | dB |
| Attenuation | dB |
| Horizontal | 200 ns/div 1 |
| Vertical | 200 mV/div 1 |
| Horizontal | 200 ns/div 2 |
| Vertical | 200 mV/div 2 |
| Configuration | |
| Pulse Level | 30KV CHARGE |
| Data Link | |

Comments:

(SYSTEM 12)

9




| | | |
|---------------|-------------|----------|
| Date | 8-5-85 | |
| Test Point | TEST D-13 | |
| Amplification | dB | |
| Attenuation | dB | |
| Horizontal | 200 | ns/div 1 |
| Vertical | 200 | mV/div 1 |
| Horizontal | 200 | ns/div 2 |
| Vertical | 200mV | ns/div 2 |
| Configuration | | |
| Pulse Level | 30KV CHARGE | |
| Data Link | | |

Comments:

(SYSTEM 13)

10

50 KV/M




| | | |
|---------------|---------------|----------|
| Date | 8-5-85 | |
| Test Point | TEST D 14 | |
| Amplification | dB | |
| Attenuation | dB | |
| Horizontal | 200 | ns/div 1 |
| Vertical | 200 | mV/div 1 |
| Horizontal | 200 | ns/div 2 |
| Vertical | 200mV | ns/div 2 |
| Configuration | | |
| Pulse Level | 30KV - CHARGE | |
| Data Link | | |

Comments:

(SYSTEM 7)

11




| | | | |
|---------------|-------------|--------|---|
| Date | 8-5-85 | | |
| Test Point | TEST D-15 | | |
| Amplification | dB | | |
| Attenuation | dB | | |
| Horizontal | 200 | ns/div | 1 |
| Vertical | 200 | mV/div | 1 |
| Horizontal | 200 | ns/div | 2 |
| Vertical | 200 MV | mV/div | 2 |
| Configuration | | | |
| Pulser Level | 30KV-CHARGE | | |
| Data Link | | | |

Comments:

(SYSTEM 14)

12


50 KV/m



| | | | |
|---------------|----|--------|---|
| Date | | | |
| Test Point | | | |
| Amplification | dB | | |
| Attenuation | dB | | |
| Horizontal | | ns/div | 1 |
| Vertical | | mV/div | 1 |
| Horizontal | | ns/div | 2 |
| Vertical | | ns/div | 2 |
| Configuration | | | |
| Pulser Level | | | |
| Data Link | | | |
| Comments: | | | |


| | | | |
|---------------|--------------------|---|--|
| Date | August 6, 1985 | | |
| Test Point | Pulser Calibration | | |
| Amplification | dB | | |
| Attenuation | dB | | |
| Horizontal | 200 ns/div | 1 | |
| Vertical | 200 mV/div | 1 | |
| Horizontal | 200 ns/div | 2 | |
| Vertical | 200 mV/div | 2 | |
| Configuration | | | |
| Pulser Level | 30KV Charge | | |
| Data Link | | | |
| Comments: | | | |

①




| | | | |
|---------------|----------------|---|--|
| Date | August 6, 1985 | | |
| Test Point | S10V TEST BOX | | |
| Amplification | dB | | |
| Attenuation | dB | | |
| Horizontal | 200 ns/div | 1 | |
| Vertical | 1000 mV/div | 1 | |
| Horizontal | 200 ns/div | 2 | |
| Vertical | 200 mV/div | 2 | |
| Configuration | | | |
| Pulser Level | 30KV Charge | | |
| Data Link | | | |
| Comments: | | | |

②




Date August 6, 1985
 Test Point S10V TEST Box
 Amplification dB
 Attenuation dB
 Horizontal 200 ns/div 1
 Vertical 1000 mV/div 1
 Horizontal 200 ns/div 2
 Vertical 200 mV/div 2
 Configuration
 Pulsar Level 30KV charge
 Data Link
 Comments:

(3)




Date August 6, 1985
 Test Point S10V TEST BOX
 Amplification dB
 Attenuation dB
 Horizontal 200 ns/div 1
 Vertical 1000 mV/div 1
 Horizontal 200 ns/div 2
 Vertical 200 mV/div 2
 Configuration
 Pulsar Level 30 KV charge
 Data Link
 Comments:

(4)




| | |
|---------------|-----------------|
| Date | August 6, 1985 |
| Test Point | 510V - Box Test |
| Amplification | dB |
| Attenuation | dB |
| Horizontal | 200 ns/div 1 |
| Vertical | 1000 mV/div 1 |
| Horizontal | 200 ns/div 2 |
| Vertical | 200 mV/div 2 |
| Configuration | |
| Pulse Level | 30 KV Charge |
| Data Link | |
| Comments: | |



(5)

CT-2 Pickup - On bottom of 50 Ω Resistor to Ground
After 510V Box

| | |
|---------------|----------------|
| Date | August 6, 1985 |
| Test Point | FCC -250-300 |
| Amplification | dB |
| Attenuation | dB |
| Horizontal | 200 ns/div 1 |
| Vertical | 1000 mV/div 1 |
| Horizontal | 200 ns/div 2 |
| Vertical | 200 mV/div 2 |
| Configuration | |
| Pulse Level | 30 KV Charge |
| Data Link | |
| Comments: | |




Fischer Device Test

(6)

CT-2 Same as above


Date August 6, 1985
 Test Point REF ANTENNA
 Amplification dB
 Attenuation dB
 Horizontal 200 ns/div 1
 Vertical 1000 mV/div 1
 Horizontal 200 ns/div 2
 Vertical 200 mV/div 2
 Configuration
 Pulse Level 30KV charge
 Data Link
 Comments:



(7)

SAME AS 6 NO PROTECTION

Date August 6, 85
 Test Point REF ANTENNA
 Amplification dB
 Attenuation dB
 Horizontal 200 ns/div 1
 Vertical 1000 mV/div 1
 Horizontal 200 ns/div 2
 Vertical 200 mV/div 2
 Configuration
 Pulse Level 30KV charge
 Data Link
 Comments:



(8)

Date August 6, 1985

Test Point

Amplification dB

Attenuation dB

Horizontal 200 ns/div 1

Vertical 1000 mV/div 1

Horizontal 200 ns/div 2

Vertical 200 mV/div 2


Configuration

Pulse Level 30KV Charge

Data Link

Comments:

(9)



Date August 6, 1985

Test Point

Amplification dB

Attenuation dB

Horizontal 200 ns/div 1

Vertical 1000 mV/div 1

Horizontal 200 ns/div 2

Vertical 200 mV/div 2


Configuration

Pulse Level 30KV Charge

Data Link

Comments:


(10)



Date August 6, 1985
 Test Point RF ANTENNA
 Amplification dB
 Attenuation 40 dB
 Horizontal 200 ns/div 1
 Vertical 1000 mV/div 1
 Horizontal 200 ns/div 2
 Vertical 200 mV/div 2
 Configuration
 Pulsar Level 30KV charge
 Data Link
 Comments:

(11)


UPPER: RF ANTENNA - 100A/div - PROBE 91550 -
 PROBE OVER WIRE ABOVE RESISTOR -
 PEAK ~ 210 A (10.5 KV)
 40 dB



Date August 6, 1985
 Test Point PULSER
 Amplification dB
 Attenuation dB
 Horizontal 200 ns/div 1
 Vertical 200 mV/div 1
 Horizontal 200 ns/div 2
 Vertical 200 mV/div 2
 Configuration
 Pulsar Level 30KV charge
 Data Link
 Comments:

(12)

UPPER: ROUND H SENSOR DIRECT 0.2V/div.
 LOWER: RECTANGULAR H SENSOR F.O. 0.2V/div.



Date August 6, 1985

Test Point

Amplification dB

Attenuation dB

Horizontal 200 ns/div 1

Vertical 200 mV/div 1

Horizontal 200 ns/div 2

Vertical 200 mV/div 2


Configuration

Pulse Level 30KV Charge

Data Link

Comments:

(13)



Date August 6, 1985

Test Point

Amplification dB

Attenuation dB

Horizontal 200 ns/div 1

Vertical 100 mV/div 1

Horizontal 200 ns/div 2

Vertical 200 mV/div 2


Configuration

Pulse Level 30KV Charge

Data Link

Comments:

(14)



LOWER: F.O. RECT. SENSOR

Date August 6, 1985

Test Point

Amplification dB

Attenuation dB

Horizontal 200 ns/div 1

Vertical 100 mV/div 1

Horizontal 200 ns/div 2


Vertical 200 mV/div 2

Configuration

Pulse Level 30 KV/charge

Data Link

Comments:



(15)

REPEAT 14

Date August 6, 1985

Test Point

Amplification dB

Attenuation dB

Horizontal 200 ns/div 1

Vertical 100 mV/div 1

Horizontal 200 ns/div 2


Vertical 200 mV/div 2

Configuration

Pulse Level 30 KV/charge

Data Link


Comments:



(16)

REPEAT 14


| | |
|---------------|----------------|
| Date | August 6, 1985 |
| Test Point | RF ANTENNA |
| Amplification | dB |
| Attenuation | 40 dB |
| Horizontal | 200 ns/div 1 |
| Vertical | 100 mV/div 1 |
| Horizontal | 200 ns/div 2 |
| Vertical | 1000 mV/div 2 |
| Configuration | |
| Pulse Level | 30 KV Charge |
| Data Link | |
| Comments: | |



(17)

UPPER: 91550 OVER RF ANTENNA ABOVE 50 OHM
RESISTOR - 40 dB 1V/div
230 A (11.5 KV)


| | |
|---------------|----------------|
| Date | August 6, 1985 |
| Test Point | RF ANTENNA |
| Amplification | dB |
| Attenuation | 40 dB |
| Horizontal | 200 ns/div 1 |
| Vertical | 100 mV/div 1 |
| Horizontal | 200 ns/div 2 |
| Vertical | 1000 mV/div 2 |
| Configuration | |
| Pulse Level | 30 KV Charge |
| Data Link | |
| Comments: | |



(18)

REPEAT (17)
240 A (12 KV)

Date August 6, 1985
 Test Point RF ANTENNA
 Amplification dB
 Attenuation dB
 Horizontal 200 ns/div 1
 Vertical 100 mV/div 1
 Horizontal 200 ns/div 2
 Vertical 50 mV/div 2
 Configuration
 Pulsar Level 30 KV charge
 Data Link
 Comments:




(19)

PEARSON 110 PROBE OVER RF ANTENNA ABOVE
 50 OHM RESISTOR

BAD TRIGGER


Date August 6, 1985
 Test Point RF ANTENNA
 Amplification dB
 Attenuation dB
 Horizontal 100 ns/div 1
 Vertical 100 mV/div 1
 Horizontal 100 ns/div 2
 Vertical 100 mV/div 2
 Configuration
 Pulsar Level 30 KV charge
 Data Link
 Comments:



(20)

REPEAT 19


| | | | |
|---------------|----------------|---|--|
| Date | August 6, 1985 | | |
| Test Point | RF ANTENNA | | |
| Amplification | dB | | |
| Attenuation | dB | | |
| Horizontal | 100 ns/div | 1 | |
| Vertical | 100 mV/div | 1 | |
| Horizontal | 100 ns/div | 2 | |
| Vertical | 100 mV/div | 2 | |
| Configuration | | | |
| Pulse Level | 30KV Charge | | |
| Data Link | | | |
| Comments: | | | |



(21)

LOWER TRACE - REPLACED F.O. TRANSMITTER


| | | | |
|---------------|----------------|---|--|
| Date | August 6, 1985 | | |
| Test Point | | | |
| Amplification | dB | | |
| Attenuation | dB | | |
| Horizontal | 50 ns/div | 1 | |
| Vertical | 100 mV/div | 1 | |
| Horizontal | 50 ns/div | 2 | |
| Vertical | 50 mV/div | 2 | |
| Configuration | | | |
| Pulse Level | 20KV Charge | | |
| Data Link | | | |
| Comments: | | | |



(22)

20KV CHARGE -


| | | | |
|---------------|-------------------|---|--|
| Date | August 6, 1985 | | |
| Test Point | SIN V RF TEST BOX | | |
| Amplification | dB | | |
| Attenuation | dB | | |
| Horizontal | 50 ns/div | 1 | |
| Vertical | 100 mV/div | 1 | |
| Horizontal | 50 ns/div | 2 | |
| Vertical | 50 mV/div | 2 | |
| Configuration | | | |
| Pulse Level | 30 KV/charge | | |
| Data Link | | | |
| Comments: | | | |



(23)

UPPER: PEARSON PROBE -
220 A


| | | | |
|---------------|----------------|---|--|
| Date | August 6, 1985 | | |
| Test Point | FCC-250-300 | | |
| Amplification | dB | | |
| Attenuation | dB | | |
| Horizontal | 50 ns/div | 1 | |
| Vertical | 100 mV/div | 1 | |
| Horizontal | 50 ns/div | 2 | |
| Vertical | 50 mV/div | 2 | |
| Configuration | | | |
| Pulse Level | 30 KV/charge | | |
| Data Link | | | |
| Comments: | | | |



(24)

FISCHER FCC-250-300 WIRE IN CIRCUIT
220 A


Date August 6, 1985
 Test Point PROBE
 Amplification dB
 Attenuation dB
 Horizontal 50 ns/div 1
 Vertical 100 mV/div 1
 Horizontal 50 ns/div 2
 Vertical 50 mV/div 2
 Configuration
 Pulser Level 30KV/charge
 Data Link
 Comments:



(25)

PROBE CHECK - NO DEVICE IN CIRCUIT - WIRE
 ANTENNA THROUGH COAX + PROBE
 PULSER PRE FIRED -

Date August 6, 1985
 Test Point
 Amplification dB
 Attenuation dB
 Horizontal 50 ns/div 1
 Vertical 100 mV/div 1
 Horizontal 50 ns/div 2
 Vertical 50 mV/div 2
 Configuration
 Pulser Level 30KV/charge
 Data Link
 Comments:



(26)

SAME AS (25)


| | | | |
|---------------|----------------|--------|---|
| Date | August 6, 1985 | | |
| Test Point | E-1 | | |
| Amplification | dB | | |
| Attenuation | dB | | |
| Horizontal | 50 | ns/div | 1 |
| Vertical | 100 | mV/div | 1 |
| Horizontal | | ns/div | 2 |
| Vertical | | mV/div | 2 |
| Configuration | | | |
| Pulse Level | 30KV Charge | | |
| Data Link | | | |
| Comments: | | | |

SYSTEM 2

(27)

510V RF TEST BOX

H FIELD TRACE



| | | | |
|---------------|----------------|--------|---|
| Date | August 6, 1985 | | |
| Test Point | E-2 | | |
| Amplification | dB | | |
| Attenuation | dB | | |
| Horizontal | 50 | ns/div | 1 |
| Vertical | 100 | mV/div | 1 |
| Horizontal | | ns/div | 2 |
| Vertical | | mV/div | 2 |
| Configuration | | | |
| Pulse Level | 30KV Charge | | |
| Data Link | | | |
| Comments: | | | |


SYSTEM 2

(28)

REPEAT

(27)

10.374MHz TX




Date August 6, 1985
 Test Point E-3
 Amplification dB
 Attenuation dB
 Horizontal 50 ns/div 1
 Vertical 100 mV/div 1
 Horizontal ns/div 2
 Vertical mV/div 2
 Configuration
 Pulse Level 30KV Charge
 Data Link

Comments:

(SYSTEM 2)

(29)

FISCHER PROTECTIVE DEVICE FCC - 250-300-UMF




Date
 Test Point
 Amplification dB
 Attenuation dB
 Horizontal ns/div 1
 Vertical mV/div 1
 Horizontal ns/div 2
 Vertical mV/div 2
 Configuration
 Pulse Level
 Data Link
 Comments:

PULSER CALIBRATION


Date 8-7-85
 Test Point DAILY CALIBRATION
 Amplification dB
 Attenuation - dB
 Horizontal 200 ns/div 1
 Vertical 200 mV/div 1
 Horizontal 200 ns/div 2
 Vertical 100 mV μ s/div 2
 Configuration
 Pulsar Level 30KV charge
 Data Link 1-COAX-2 F.O.
 Comments:
 F.O. ATTN-20dB

1



Date 8-7-85
 Test Point DAILY CALIBRATION
 Amplification dB
 Attenuation dB
 Horizontal 200 ns/div 1
 Vertical 200 mV/div 1
 Horizontal 200 ns/div 2
 Vertical 100 mV μ s/div 2
 Configuration
 Pulsar Level 30KV-CHARGE
 Data Link
 Comments:
 F.O. ATTN 20dB-

2



Date August 7, 1985
 Test Point D-15
 Amplification dB
 Attenuation dB
 Horizontal 200 ns/div 1
 Vertical 200 mV/div 1
 Horizontal 200 ns/div 2
 Vertical 100 mV/div 2
 Configuration
 Pulsar Level 30KV/charge
 Data Link


Comments:

SYSTEM 2

(3)

ALPHA DELTA RT - PROTECTIVE DEVICE

TRACES: PULSER FIELDS




Date August 7, 1985
 Test Point D15T
 Amplification dB
 Attenuation dB
 Horizontal 200 ns/div 1
 Vertical 200 mV/div 1
 Horizontal 200 ns/div 2
 Vertical 100 mV/div 2
 Configuration
 Pulsar Level 30 KV/charge
 Data Link


Comments:

SYSTEM 2

(4)




Date 8-7-85
 Test Point F-L
 Amplification dB
 Attenuation dB
 Horizontal 50 ns/div 1
 Vertical 200 mV/div 1
 Horizontal 50 ns/div 2
 Vertical 100 ns/div 2
 Configuration
 Pulsar Level 30 KV -CHARGE
 Data Link
 Comments:
 FIELD 50 KV/M



20

SYSTEM 2 - Power on - RECEIVE MODE -
 PROTECTION ON A.C. POWER - DEVICE (TP 39)
NO PROTECTION ON R.F. ANTENNA INJECT.

Date 8-7-85
 Test Point F-2
 Amplification dB
 Attenuation dB
 Horizontal 50 ns/div 1
 Vertical 200 mV/div 1
 Horizontal 50 ns/div 2
 Vertical 100 mV/div 2
 Configuration
 Pulsar Level 30 KV -CHARGE
 Data Link
 Comments:
 FIELD 50 KV/M



21


SYSTEM 2 POWER ON - TRANSMIT MODE
 A.C. POWER PROTECTION - DEVICE (TP 39)
 NO PROTECTION ON RF ANTENNA.
 TX - TUNED TO 10.374 MHz.

| | |
|---------------|--------------|
| Date | 8-7-85 |
| Test Point | F-3 |
| Amplification | dB |
| Attenuation | dB |
| Horizontal | 200 ns/div 1 |
| Vertical | 200 mV/div 1 |
| Horizontal | 200 ns/div 2 |
| Vertical | 100 mV/div 2 |
| Configuration | |
| Pulse Level | 30 KV DRIVE |
| Data Link | |

Comments:

50 KV/M • FIELD

22




SYSTEM 2 - NO PROTECTION ON AC POWER OR RF ANTENNA
HONDA GENERATOR PROTECTED BY TP 39.
RECEIVE MODE

| | |
|---------------|---------------|
| Date | 8-7-85 |
| Test Point | F-4 |
| Amplification | dB |
| Attenuation | dB |
| Horizontal | 200 ns/div 1 |
| Vertical | 200 mV/div 1 |
| Horizontal | 200 ns/div 2 |
| Vertical | 100 mV/div 2 |
| Configuration | |
| Pulse Level | 30 KV - DRIVE |
| Data Link | |

Comments:

50 KV/M FIELD


23



SYSTEM 2

TRANSMIT MODE - NO PROTECTION ON
AC POWER OR RF INJECT -
TUNED TO 10.374 MHz -


Date 8-7-85
 Test Point PROBE-91550-4
 Amplification dB
 Attenuation 40 dB
 Horizontal 200 ns/div 1
 Vertical 50 mV/div 1
 Horizontal 200 ns/div 2
 Vertical 100mV 40/div 2
 Configuration
 Pulsar Level 30KV - DRIVE
 Data Link
 Comments:



FIELD 50KV/m 24
100 A PER DIVISION

PROBE TEST - WITH NO WIRE THROUGH CENTER -

Date 8-7-85
 Test Point RF WIRE ANTENNA
 Amplification dB
 Attenuation 40 dB
 Horizontal 200 ns/div 1
 Vertical 50 mV/div 1
 Horizontal 200 ns/div 2
 Vertical 100 mV 40/div 2
 Configuration
 Pulsar Level 30KV - CHARGE
 Data Link
 Comments:



FIELD 50 KV/m
 UPPER TRACE 80A 25
(4.0KV)

PROBE 91550-4 - WITH RF ANTENNA THROUGH CENTER
 WITH 50 Ω RESISTOR TO GROUND.

FIELD 1.6 divisions, CURRENT 1.6 div -

Date 8-7-85
 Test Point RF-WIRE ANTENNA
 Amplification dB
 Attenuation dB
 Horizontal 200 ns/div 1
 Vertical 20 mV/div 1
 Horizontal 200 ns/div 2
 Vertical 100 MV dB/div 2
 Configuration
 Pulsar Level 20KV-CHARGE
 Data Link

Comments:


FIELD 1.1 dw

CURRENT 3.6 div

I = 80 A (4KV)

26

RF WIRE ANTENNA THROUGH 50 Ω RESISTOR TO GROUND
 MEASURED WITH SINGER I PROBE 91550-4.



Date 8-7-85
 Test Point RF WIRE ANTENNA
 Amplification dB
 Attenuation dB
 Horizontal 200 ns/div 1
 Vertical 20 mV/div 1
 Horizontal 200 ns/div 2
 Vertical 100 MV dB/div 2
 Configuration
 Pulsar Level 30KV-CHARGE
 Data Link

Comments:


FIELD - 1.6 divisions

CURRENT - 1.6 div.

I = -80 A (4KV)

27

REVERSED PROBE TEST SAME AS PHOTO 25




Date 8-7-85
 Test Point RF ANTENNA
 Amplification dB
 Attenuation dB
 Horizontal 200 ns/div 1
 Vertical 50 mV/div 1
 Horizontal 200 ns/div 2
 Vertical 100mV/div 2
 Configuration
 Pulsar Level 30KV-CHARGE
 Data Link

Comments:

FD 16cliv

28

RF ANTENNA CURRENT TO GROUND - THROUGH COAX +
 50 Ω RESISTOR - DIRECTLY OVER RF ANTENNA
 IN FRONT OF COAX -
 CURRENT - OFF SCALE - 200 A (10KV+)




Date 8-7-85
 Test Point RF WIRE ANT -
 Amplification dB
 Attenuation dB
 Horizontal 200 ns/div 1
 Vertical 100 mV/div 1
 Horizontal 200 ns/div 2
 Vertical 100mV/div 2
 Configuration
 Pulsar Level 30KV charge
 Data Link

Comments:


29

270 A (13.5 KV)

MEASUREMENT OF RF WIRE ANTENNA
 BEFORE COAX - ~~50.0HM~~ 50.0HM RESISTOR TO GND.




Date August 7, 1985
 Test Point RF WIRE ANTENNA
 Amplification dB
 Attenuation dB
 Horizontal 200 ns/div 1
 Vertical 100 mV/div 1
 Horizontal 200 ns/div 2
 Vertical 100 mV/div 2
 Configuration
 Pulse Level 30 KV Charge
 Data Link
 Comments:




REPEAT (29) (30) - I = 290 A (14.5 KV)

Date August 7, 1985
 Test Point RF WIRE ANTENNA
 Amplification dB
 Attenuation dB
 Horizontal 200 ns/div 1
 Vertical 100 mV/div 1
 Horizontal 200 ns/div 2
 Vertical 100 mV/div 2
 Configuration
 Pulse Level 30 KV Charge
 Data Link
 Comments:



(13.25 KV)
 265 A (31)
 REMOVED COAX FROM CIRCUIT - LOOKING
 AT RF ANTENNA - UHF CONNECTOR STILL IN
 CIRCUIT


Date August 7, 1985
 Test Point RF WIRE ANT
 Amplification dB
 Attenuation dB
 Horizontal 200 ns/div 1
 Vertical 100 mV/div 1
 Horizontal 200 ns/div 2
 Vertical 100 mV/div 2
 Configuration
 Pulsar Level 30 KV Charge
 Data Link
 Comments:



(32)

REPEAT (31) BUT WITH ANTENNA DIRECT TO
 50 OHM RESISTOR TO GROUND. NO
 HARDWARE BETWEEN ANTENNA + RESISTOR
 275 A (13.75KV)


Date August 7, 1985
 Test Point RF WIRE ANT
 Amplification dB
 Attenuation dB
 Horizontal 200 ns/div 1
 Vertical 100 mV/div 1
 Horizontal 200 ns/div 2
 Vertical 100 mV/div 2
 Configuration
 Pulsar Level 20KV Charge
 Data Link
 Comments:



(33)

REPEAT (32) 20KV-CHARGE. $I = 170A$ (8.5KV)

Date August 7, 1985
 Test Point RF ANTENNA
 Amplification dB
 Attenuation dB
 Horizontal 200 ns/div 1
 Vertical 100 mV/div 1
 Horizontal 200 ns/div 2
 Vertical 100 mV/div 2
 Configuration
 Pulsar Level 30KV Charge
 Data Link
 Comments:




(34)

PROBE 94456-3

I = 260A (13.0KV)

Date August 7, 1985
 Test Point RF ANTENNA
 Amplification dB
 Attenuation dB
 Horizontal 200 ns/div 1
 Vertical 100 mV/div 1
 Horizontal 200 ns/div 2
 Vertical 100 mV/div 2
 Configuration
 Pulsar Level 20KV Charge
 Data Link
 Comments:




(35)


REPEAT (34) 20KV CHARGE

I = 180A (9.0KV)


| | | | |
|---------------|------------------|---|--|
| Date | August 7, 1985 | | |
| Test Point | | | |
| Amplification | dB | | |
| Attenuation | dB | | |
| Horizontal | 200 ns/div | 1 | |
| Vertical | 100 mV/div | 1 | |
| Horizontal | 200 ns/div | 2 | |
| Vertical | 100 mV/div | 2 | |
| Configuration | | | |
| Pulse Level | 30KV Charge | | |
| Data Link | | | |
| Comments: | (SYSTEM 11) (36) | | |



| | | | |
|---------------|------------------|---|--|
| Date | August 7, 1985 | | |
| Test Point | D17R | | |
| Amplification | dB | | |
| Attenuation | dB | | |
| Horizontal | 200 ns/div | 1 | |
| Vertical | 100 mV/div | 1 | |
| Horizontal | 200 ns/div | 2 | |
| Vertical | 100 mV/div | 2 | |
| Configuration | | | |
| Pulse Level | 30KV Charge | | |
| Data Link | | | |
| Comments: | (System 11) (37) | | |




Date August 7, 1985
 Test Point D17T
 Amplification dB
 Attenuation dB
 Horizontal 200 ns/div 1
 Vertical 100 mV/div 1
 Horizontal 200 ns/div 2
 Vertical 100 mV/div 2
 Configuration
 Pulsar Level 30 KV Charge
 Data Link
 Comments:




(38)
 REPEAT (37) TRANSMIT

Date August 7, 1985
 Test Point D17R2
 Amplification dB
 Attenuation dB
 Horizontal 200 ns/div 1
 Vertical 100 mV/div 1
 Horizontal 200 ns/div 2
 Vertical 100 mV/div 2
 Configuration
 Pulsar Level 30KV Charge
 Data Link
 Comments:




(SYSTEM 11) (39)

| | |
|---------------|----------------|
| Date | August 8, 1985 |
| Test Point | CALIBRATION |
| Amplification | dB |
| Attenuation | dB |
| Horizontal | 200 ns/div 1 |
| Vertical | 200 mV/div 1 |
| Horizontal | 200 ns/div 2 |
| Vertical | 100 mV/div 2 |
| Configuration | |
| Pulse Level | 30 KV charge |
| Date Link | |
| Comments: | |



(2)
PULSER CALIBRATION -

| | |
|---------------|----------------|
| Date | August 8, 1985 |
| Test Point | E-5 |
| Amplification | dB |
| Attenuation | dB |
| Horizontal | 200 ns/div 1 |
| Vertical | 200 mV/div 1 |
| Horizontal | 200 ns/div 2 |
| Vertical | 100 mV/div 2 |
| Configuration | |
| Pulse Level | 30 KV charge |
| Date Link | |
| Comments: | |




SYSTEM 11

(3)


| | | | |
|---------------|--------------|---|--|
| Date | August 8, 85 | | |
| Test Point | E6 | | |
| Amplification | dB | | |
| Attenuation | dB | | |
| Horizontal | 200 ns/div | 1 | |
| Vertical | 200 mV/div | 1 | |
| Horizontal | 200 ns/div | 2 | |
| Vertical | 100 mV/div | 2 | |
| Configuration | | | |
| Pulse Level | 30KV Charge | | |
| Data Link | | | |
| Comments: | SYSTEM II | | |

(4)



| | | | |
|---------------|----------------|---|--|
| Date | August 8, 1985 | | |
| Test Point | E7 | | |
| Amplification | dB | | |
| Attenuation | dB | | |
| Horizontal | 200 ns/div | 1 | |
| Vertical | 200 mV/div | 1 | |
| Horizontal | 200 ns/div | 2 | |
| Vertical | 100 mV/div | 2 | |
| Configuration | | | |
| Pulse Level | 30KV Charge | | |
| Data Link | | | |
| Comments: | SYSTEM II | | |

(5)




Date August 8, 1985
 Test Point E8
 Amplification dB
 Attenuation dB
 Horizontal 200 ns/div 1
 Vertical 200 mV/div 1
 Horizontal 200 ns/div 2
 Vertical 100 mV/div 2
 Configuration
 Pulse Level 30KV Charge
 Data Link

Comments:

SYSTEM - 11


(6)




Date August 8, 1985
 Test Point E-9
 Amplification dB
 Attenuation dB
 Horizontal 200 ns/div 1
 Vertical 200 mV/div 1
 Horizontal 200 ns/div 2
 Vertical 100 mV/div 2
 Configuration
 Pulse Level 30KV Charge
 Data Link

Comments:


(7)



| | |
|---------------|-----------------|
| Date | 8 August, 1985 |
| Test Point | E-10 |
| Amplification | dB |
| Attenuation | dB |
| Horizontal | 200 ns/div 1 |
| Vertical | 200 mV/div 1 |
| Horizontal | 200 ns/div 2 |
| Vertical | 100mV/div 2 |
| Configuration | |
| Pulse Level | 30KV Charge |
| Data Link | |
| Comments: | (SYSTEM 11) (8) |




| | |
|---------------|----------------|
| Date | August 8, 1985 |
| Test Point | E-11 |
| Amplification | dB |
| Attenuation | dB |
| Horizontal | 200 ns/div 1 |
| Vertical | 200 mV/div 1 |
| Horizontal | 200 ns/div 2 |
| Vertical | 100mV/div 2 |
| Configuration | |
| Pulse Level | 30KV Charge |
| Data Link | |
| Comments: | SYSTEM 11 (9) |




| | |
|---------------|----------------|
| Date | August 8, 1985 |
| Test Point | D18R |
| Amplification | dB |
| Attenuation | dB |
| Horizontal | 200 ns/div 1 |
| Vertical | 200 mV/div 1 |
| Horizontal | 200 ns/div 2 |
| Vertical | 100 mV/div 2 |
| Configuration | |
| Pulse Level | 30KV charge |
| Data Link | |
| Comments: | SYSTEM 11 |

(10)




| | |
|---------------|----------------|
| Date | August 8, 1985 |
| Test Point | D18T |
| Amplification | dB |
| Attenuation | dB |
| Horizontal | 200 ns/div 1 |
| Vertical | 200 mV/div 1 |
| Horizontal | 200 ns/div 2 |
| Vertical | 100 mV/div 2 |
| Configuration | |
| Pulse Level | 30KV charge |
| Data Link | |
| Comments: | SYSTEM 11 |


(11)




Date Aug 8, 1985
 Test Point D-19
 Amplification dB
 Attenuation dB
 Horizontal 200 ns/div 1
 Vertical 200 mV/div 1
 Horizontal 200 ns/div 2
 Vertical 100 mV/div 2
 Configuration
 Pulsar Level 30KV charge
 Data Link
 Comments:
 SYSTEM 3 (12)




Date August 8, 1985
 Test Point D20
 Amplification dB
 Attenuation dB
 Horizontal 200 ns/div 1
 Vertical 200 mV/div 1
 Horizontal 200 ns/div 2
 Vertical 100 mV/div 2
 Configuration
 Pulsar Level 30KV charge
 Data Link
 Comments:
 SYSTEM 3 (13)



| | | | |
|---------------|-----------------|---|--|
| Date | August 8, 1985 | | |
| Test Point | D21 | | |
| Amplification | dB | | |
| Attenuation | dB | | |
| Horizontal | 200 ns/div | 1 | |
| Vertical | 200 mV/div | 1 | |
| Horizontal | 200 ns/div | 2 | |
| Vertical | 100 mV/div | 2 | |
| Configuration | | | |
| Pulse Level | 30KV charge | | |
| Date Link | | | |
| Comments: | (SYSTEM 3) (14) | | |




| | | | |
|---------------|-----------------|---|--|
| Date | August 8, 1985 | | |
| Test Point | D22 | | |
| Amplification | dB | | |
| Attenuation | dB | | |
| Horizontal | 200 ns/div | 1 | |
| Vertical | 200 mV/div | 1 | |
| Horizontal | 200 ns/div | 2 | |
| Vertical | 100 mV/div | 2 | |
| Configuration | | | |
| Pulse Level | 30KV charge | | |
| Date Link | | | |
| Comments: | (SYSTEM 3) (15) | | |




Date 8 August, 1985
 Test Point E12
 Amplification dB
 Attenuation dB
 Horizontal 200 ns/div 1
 Vertical 200 mV/div 1
 Horizontal 200 ns/div 2
 Vertical 100 mV/div 2
 Configuration
 Pulse Level 30KV Charge
 Data Link

Comments:
 (SYSTEM 3) (16)




Date August 8, 1985
 Test Point E13
 Amplification dB
 Attenuation dB
 Horizontal 200 ns/div 1
 Vertical 200 mV/div 1
 Horizontal 200 ns/div 2
 Vertical 100 mV/div 2
 Configuration
 Pulse Level 30KV Charge
 Data Link

Comments:
 (SYSTEM 3) (17)




Date August 8, 1985
 Test Point E-14
 Amplification dB
 Attenuation dB
 Horizontal 200 ns/div 1
 Vertical 200 mV/div 1
 Horizontal 200 ns/div 2
 Vertical 100 mV/div 2
 Configuration
 Pulse Level 30KV/Charge
 Data Link
 Comments:
 (SYSTEM 3) (18)




(TEST E15 NO PHOTO)


Date August 8, 1985
 Test Point E16
 Amplification dB
 Attenuation dB
 Horizontal 200 ns/div 1
 Vertical 200 mV/div 1
 Horizontal 200 ns/div 2
 Vertical 100 mV/div 2
 Configuration
 Pulse Level
 Data Link
 Comments:
 (SYSTEM 11) (19)



Date August 8, 1985
 Test Point E17
 Amplification dB
 Attenuation dB
 Horizontal 200 ns/div 1
 Vertical 200 mV/div 1
 Horizontal 200 ns/div 2
 Vertical 100 mV/div 2
 Configuration
 Pulsar Level 30 KV Charge
 Data Link
 Comments:
 (SYSTEM 10) (20)



Date August 8, 1985
 Test Point F5R
 Amplification dB
 Attenuation dB
 Horizontal 200 ns/div 1
 Vertical 200 mV/div 1
 Horizontal 200 ns/div 2
 Vertical 100 mV/div 2
 Configuration
 Pulsar Level 30 KV Charge
 Data Link
 Comments:
 (SYSTEM 10) (21)



Date August 8, 1985

Test Point F5T

Amplification dB

Attenuation dB

Horizontal 200 ns/div 1

Vertical 200 mV/div 1

Horizontal 200 ns/div 2

Vertical 100 mV/div 2

Configuration


Pulse Level 30 KV/charge

Data Link

Comments:

(SYSTEM 10)

(22)



Date August 8, 1985

Test Point F6R

Amplification dB

Attenuation dB

Horizontal 200 ns/div 1

Vertical 200 mV/div 1

Horizontal 200 ns/div 2

Vertical 100 mV/div 2

Configuration


Pulse Level 30 KV/charge

Data Link

Comments:

(SYSTEM 10)

(23)



AD-A164 436


ELECTROMAGNETIC PULSE/TRANSIENT THREAT TESTING OF
PROTECTION DEVICES FOR (U) ELECTROSPACE SYSTEMS INC
ARLINGTON VA D BODSON ET AL 31 OCT 85


272

UNCLASSIFIED


NCS-T18-85-10-VOL-3-SEC-5 DCA100-85-C-0010 F/G 20/14

NL







| | | | |
|---------------|------------------|---|--|
| Date | August 8, 1985 | | |
| Test Point | F6T | | |
| Amplification | dB | | |
| Attenuation | dB | | |
| Horizontal | 200 ns/div | 1 | |
| Vertical | 200 mV/div | 1 | |
| Horizontal | 200 ns/div | 2 | |
| Vertical | 100 mV/div | 2 | |
| Configuration | | | |
| Pulse Level | 30KV Charge | | |
| Data Link | | | |
| Comments: | (SYSTEM 10) (24) | | |




| | | | |
|---------------|------------------|---|--|
| Date | August 8, 1985 | | |
| Test Point | F7R | | |
| Amplification | dB | | |
| Attenuation | dB | | |
| Horizontal | 200 ns/div | 1 | |
| Vertical | 200 mV/div | 1 | |
| Horizontal | 200 ns/div | 2 | |
| Vertical | 100 mV/div | 2 | |
| Configuration | | | |
| Pulse Level | 30KV Charge | | |
| Data Link | | | |
| Comments: | (SYSTEM 11) (25) | | |




| | | | |
|---------------|------------------|---|--|
| Date | August 8, 1985 | | |
| Test Point | E7T | | |
| Amplification | dB | | |
| Attenuation | dB | | |
| Horizontal | 200 ns/div | 1 | |
| Vertical | 200 mV/div | 1 | |
| Horizontal | 200 ns/div | 2 | |
| Vertical | 100 mV/div | 2 | |
| Configuration | | | |
| Pulse Level | 30KV Charge | | |
| Data Link | | | |
| Comments: | (SYSTEM 11) (26) | | |




| | | | |
|---------------|-----------------|---|--|
| Date | August 8, 1985 | | |
| Test Point | F8R | | |
| Amplification | dB | | |
| Attenuation | dB | | |
| Horizontal | 200 ns/div | 1 | |
| Vertical | 200 mV/div | 1 | |
| Horizontal | 200 ns/div | 2 | |
| Vertical | 100 mV/div | 2 | |
| Configuration | | | |
| Pulse Level | 30KV Charge | | |
| Data Link | | | |
| Comments: | (SYSTEM 1) (27) | | |




Date August 8, 1985
 Test Point F8T
 Amplification dB
 Attenuation dB
 Horizontal 200 ns/div 1
 Vertical 200 mV/div 1
 Horizontal 200 ns/div 2
 Vertical 100 mV/div 2
 Configuration
 Pulsar Level 30KV/charge
 Data Link
 Comments:
 (SYSTEM L) (28)




Date August 8, 1985
 Test Point F9R
 Amplification dB
 Attenuation dB
 Horizontal 200 ns/div 1
 Vertical 200 mV/div 1
 Horizontal 200 ns/div 2
 Vertical 100 mV/div 2
 Configuration
 Pulsar Level 30KV/charge
 Data Link
 Comments:
 SYSTEM L (29)




| | | | |
|---------------|-----------------|---|--|
| Date | August 8, 1985 | | |
| Test Point | F9T | | |
| Amplification | dB | | |
| Attenuation | dB | | |
| Horizontal | 200 ns/div | 1 | |
| Vertical | 200 mV/div | 1 | |
| Horizontal | 200 ns/div | 2 | |
| Vertical | 100 mV/div | 2 | |
| Configuration | | | |
| Pulse Level | 30KV/charge | | |
| Date Link | | | |
| Comments: | (SYSTEM 1) (30) | | |




| | | | |
|---------------|-----------------|---|--|
| Date | August 8, 1985 | | |
| Test Point | F10R | | |
| Amplification | dB | | |
| Attenuation | dB | | |
| Horizontal | 200 ns/div | 1 | |
| Vertical | 200 mV/div | 1 | |
| Horizontal | 200 ns/div | 2 | |
| Vertical | 100 mV/div | 2 | |
| Configuration | | | |
| Pulse Level | 30KV/charge | | |
| Date Link | | | |
| Comments: | (SYSTEM 5) (31) | | |




Date August 8, 1985
 Test Point F10T
 Amplification dB
 Attenuation dB
 Horizontal 200 ns/div 1
 Vertical 200 mV/div 1
 Horizontal 200 ns/div 2
 Vertical 100 mV/div 2
 Configuration
 Pulse Level 30KV charge
 Data Link
 Comments:
(SYSTEM 5) (32)




Date August 8, 1985
 Test Point F11R
 Amplification dB
 Attenuation dB
 Horizontal 200 ns/div 1
 Vertical 200 mV/div 1
 Horizontal 200 ns/div 2
 Vertical 100 mV/div 2
 Configuration
 Pulse Level 30KV charge
 Data Link
 Comments:
(SYSTEM 5) (33)




| | |
|---------------|-----------------|
| Date | August 8, 1985 |
| Test Point | F11T |
| Amplification | dB |
| Attenuation | dB |
| Horizontal | 200 ns/div 1 |
| Vertical | 200 mV/div 1 |
| Horizontal | 200 ns/div 2 |
| Vertical | 100 mV/div 2 |
| Configuration | |
| Pulse Level | 30KV charge |
| Data Link | |
| Comments: | (SYSTEM 5) (34) |




| | |
|---------------|-----------------|
| Date | August 8, 1985 |
| Test Point | F12R |
| Amplification | dB |
| Attenuation | dB |
| Horizontal | 200 ns/div 1 |
| Vertical | 200 mV/div 1 |
| Horizontal | 200 ns/div 2 |
| Vertical | 100 mV/div 2 |
| Configuration | |
| Pulse Level | 30KV charge |
| Data Link | |
| Comments: | (SYSTEM 4) (35) |




| | | | |
|---------------|-----------------|---|--|
| Date | August 8, 1985 | | |
| Test Point | F12T | | |
| Amplification | dB | | |
| Attenuation | dB | | |
| Horizontal | 200 ns/div | 1 | |
| Vertical | 200 mV/div | 1 | |
| Horizontal | 200 ns/div | 2 | |
| Vertical | 100 mV/div | 2 | |
| Configuration | | | |
| Pulse Level | 30KV charge | | |
| Data Link | | | |
| Comments: | (SYSTEM 4) (36) | | |



| | | | |
|---------------|-----------------|---|--|
| Date | August 8, 1985 | | |
| Test Point | F13R | | |
| Amplification | dB | | |
| Attenuation | dB | | |
| Horizontal | 200 ns/div | 1 | |
| Vertical | 200 mV/div | 1 | |
| Horizontal | 200 ns/div | 2 | |
| Vertical | 100 mV/div | 2 | |
| Configuration | | | |
| Pulse Level | 30KV charge | | |
| Data Link | | | |
| Comments: | (SYSTEM 3) (37) | | |



| | |
|---------------|-----------------|
| Date | August 8, 1985 |
| Test Point | F13T |
| Amplification | dB |
| Attenuation | dB |
| Horizontal | 200 ns/div 1 |
| Vertical | 200 mV/div 1 |
| Horizontal | 200 ns/div 2 |
| Vertical | 100 mV/div 2 |
| Configuration | |
| Pulse Level | 30KV Charge |
| Data Link | |
| Comments: | (SYSTEM 3) (38) |



| | |
|---------------|----------|
| Date | |
| Test Point | |
| Amplification | dB |
| Attenuation | dB |
| Horizontal | ns/div 1 |
| Vertical | mV/div 1 |
| Horizontal | ns/div 2 |
| Vertical | mV/div 2 |
| Configuration | |
| Pulse Level | |
| Data Link | |
| Comments: | |

Date August 9, 1985

Test Point CALIBRATION

Amplification dB

Attenuation dB

Horizontal 200 ns/div 1

Vertical 200 mV/div 1

Horizontal ns/div 2


Vertical mV/div 2

Configuration

Pulse Level 30 kV Charge

Date Link

Comments:



(1)

ROUND 4 SENSOR - DIRECT

Date August 9, 1985

Test Point F14R

Amplification dB

Attenuation dB

Horizontal 200 ns/div 1

Vertical 200 mV/div 1

Horizontal ns/div 2

Vertical mV/div 2


Configuration

Pulse Level 30 kV Charge

Date Link

Comments:

(SYSTEM 16)




(2)

Date August 9, 1985
 Test Point F15R
 Amplification dB
 Attenuation dB
 Horizontal 200 ns/div 1
 Vertical 200 mV/div 1
 Horizontal ns/div 2
 Vertical mV-ns/div 2
 Configuration
 Pulsar Level 30 KV charge
 Data Link

Comments:

(SYSTEM 16)

③




Date August 9, 1985
 Test Point F15T
 Amplification dB
 Attenuation dB
 Horizontal 200 ns/div 1
 Vertical 200 mV/div 1
 Horizontal ns/div 2
 Vertical mV-ns/div 2
 Configuration
 Pulsar Level 30 KV charge
 Data Link

Comments:

(SYSTEM 16)

④




| | |
|---------------|----------------|
| Date | August 9, 1985 |
| Test Point | F16R |
| Amplification | dB |
| Attenuation | dB |
| Horizontal | 200 ns/div 1 |
| Vertical | 200 mV/div 1 |
| Horizontal | ns/div 2 |
| Vertical | mV/div 2 |
| Configuration | |
| Pulse Level | 30KV/charge |
| Date Link | |

Comments:

(SYSTEM 14)

(5)




| | |
|---------------|----------------|
| Date | August 9, 1985 |
| Test Point | F16T |
| Amplification | dB |
| Attenuation | dB |
| Horizontal | 200 ns/div 1 |
| Vertical | 200 mV/div 1 |
| Horizontal | ns/div 2 |
| Vertical | mV/div 2 |
| Configuration | |
| Pulse Level | 30KV/charge |
| Date Link | |

Comments:

(SYSTEM 14)

(6)




| | | | |
|---------------|----------------|---|--|
| Date | 9 August, 1985 | | |
| Test Point | F17T | | |
| Amplification | dB | | |
| Attenuation | dB | | |
| Horizontal | 200 ns/div | 1 | |
| Vertical | 200 mV/div | 1 | |
| Horizontal | ns/div | 2 | |
| Vertical | mV/div | 2 | |
| Configuration | | | |
| Pulse Level | 30KV Charge | | |
| Data Link | | | |

Comments:

(SYSTEM 14)

(7)




| | | | |
|---------------|----------------|---|--|
| Date | August 9, 1985 | | |
| Test Point | F17R | | |
| Amplification | dB | | |
| Attenuation | dB | | |
| Horizontal | 200 ns/div | 1 | |
| Vertical | 200 mV/div | 1 | |
| Horizontal | ns/div | 2 | |
| Vertical | mV/div | 2 | |
| Configuration | | | |
| Pulse Level | 30KV Charge | | |
| Data Link | | | |


Comments:

(SYSTEM 14)

(8)




| | | | |
|---------------|-------------------------------------|---|--|
| Date | August 9, 1985 | | |
| Test Point | | | |
| Amplification | dB | | |
| Attenuation | 20 dB | | |
| Horizontal | 50 ns/div | 1 | |
| Vertical | 200 mV/div | 1 | |
| Horizontal | 50 ns/div | 2 | |
| Vertical | 50 mV ^{mV} /div | 2 | |
| Configuration | | | |
| Pulse Level | 30KV charge. | | |
| Date Link | | | |
| Comments: | | | |



⑨
 CURRENT THROUGH PORTABLE RUBBER DUCK ANTENNA
 NO PROTECTION - PROBE CT-2 - 50 OHMS TO GROUND -
 20dB ATTN - 200mV/div 2A div 50ns/div $\frac{+6.5A}{(325V)}$


| | | | |
|---------------|-------------------------------------|---|--|
| Date | August 9, 1985 | | |
| Test Point | | | |
| Amplification | dB | | |
| Attenuation | 20 dB | | |
| Horizontal | 50 ns/div | 1 | |
| Vertical | 200 mV/div | 1 | |
| Horizontal | 50 ns/div | 2 | |
| Vertical | 50 mV ^{mV} /div | 2 | |
| Configuration | | | |
| Pulse Level | 30KV charge | | |
| Date Link | | | |
| Comments: | | | |



REPEAT ⑨ WITH ⑩ FISCHER PROTECTOR -


7.6A (380V)

| | | | |
|---------------|--------------------------|---|--|
| Date | August 9, 1985 | | |
| Test Point | H FIELD SENSORS | | |
| Amplification | dB | | |
| Attenuation | dB | | |
| Horizontal | 200 ns/div | 1 | |
| Vertical | 200 mV/div | 1 | |
| Horizontal | 200 ns/div | 2 | |
| Vertical | 200 $\frac{mV}{ns}$ /div | 2 | |
| Configuration | | | |
| Pulse Level | 30KV Charge | | |
| Data Link | | | |
| Comments: | | | |




(11)
 H FIELD SENSORS - NEW F.O. TRANSMITTER -
 LOWER: RECT. + SENSOR F.O.
 UPPER: ROUND H SENSOR DIRECT -

| | | | |
|---------------|--------------------------|----|--|
| Date | August 9, 1985 | | |
| Test Point | | | |
| Amplification | dB | | |
| Attenuation | 20 | dB | |
| Horizontal | 200 ns/div | 1 | |
| Vertical | 200 mV/div | 1 | |
| Horizontal | 200 ns/div | 2 | |
| Vertical | 200 $\frac{mV}{ns}$ /div | 2 | |
| Configuration | | | |
| Pulse Level | 30KV Charge | | |
| Data Link | | | |
| Comments: | | | |




(12)
 RUBBER DUCK - FISCHER PROTECTOR
 CT-2 PROBE - 20dB ATTN
 2A/DIV I = 8A (400V)

Date August 9, 1985
 Test Point RUBBER DUCK
 Amplification dB
 Attenuation 20 dB
 Horizontal 50 ns/div 1
 Vertical 200 mV/div 1
 Horizontal 50 ns/div 2
 Vertical 200 ^{mV} ~~ns~~/div 2
 Configuration
 Pulse Level 30KV charge
 Data Link
 Comments:




(13)
 REPEAT (12) w 50 ns/div I = 8 A (400V)
 FISCHER DEVICE

Date August 9, 1985
 Test Point RUBBER DUCK
 Amplification dB
 Attenuation 20 dB
 Horizontal 50 ns/div 1
 Vertical 200 mV/div 1
 Horizontal 50 ns/div 2
 Vertical 200 ^{mV} ~~ns~~/div 2
 Configuration
 Pulse Level 30KV charge
 Data Link
 Comments:



(14)
 REPEAT (13) NO PROTECTOR I = ~ 5.5 A (275V)
 NO FISCHER DEVICE


| | |
|---------------|----------------------------------------|
| Date | August 9, 1985 |
| Test Point | |
| Amplification | dB |
| Attenuation | dB |
| Horizontal | 50 ns/div 1 |
| Vertical | 200 mV/div 1 |
| Horizontal | 50 ns/div 2 |
| Vertical | 200 ^{mV} mV /div 2 |
| Configuration | |
| Pulse Level | 30KV charge |
| Data Link | |
| Comments: | |



(15)

FISCHER UNIT ON BOX - NO RUBBER DUCK ANTENNA
OPENING CAPPED, NOT GROUNDED - MADE WITH
CT2-SENSOR, NOT CONNECTED TO ANTENNA SHIELDS


| | |
|---------------|------------------------------------|
| Date | August 9, 1985 |
| Test Point | |
| Amplification | dB |
| Attenuation | dB |
| Horizontal | 50 ns/div 1 |
| Vertical | 200 mV/div 1 |
| Horizontal | ns/div 2 |
| Vertical | ^{mV} mV /div 2 |
| Configuration | |
| Pulse Level | 30KV charge |
| Data Link | |
| Comments: | |



(16)

AS IN (15) EXCEPT SHIELD CONNECTED TO
CT-2 SHIELD
NO NOISE


| | |
|---------------|----------------|
| Date | August 9, 1985 |
| Test Point | |
| Amplification | dB |
| Attenuation | 20 dB |
| Horizontal | 50 ns/div 1 |
| Vertical | 200 mV/div 1 |
| Horizontal | 50 ns/div 2 |
| Vertical | 200 mV/div 2 |
| Configuration | |
| Pulse Level | 30 KV/charge |
| Data Link | |
| Comments: | |



(17)

ADDED RUBBER DUCK ANTENNA INCLUDING FISCHER
CT-2 GROUNDED - 5.6 A (280V)


| | |
|---------------|----------------|
| Date | August 9, 1985 |
| Test Point | |
| Amplification | dB |
| Attenuation | 20 dB |
| Horizontal | 50 ns/div 1 |
| Vertical | 200 mV/div 1 |
| Horizontal | 50 ns/div 2 |
| Vertical | 200 mV/div 2 |
| Configuration | |
| Pulse Level | 30 KV/charge |
| Data Link | |
| Comments: | |



(18)

ANTENNA WITHOUT FISCHER PROTECTOR -
5.6 A (280V)


| | |
|---------------|----------------|
| Date | August 9, 1985 |
| Test Point | |
| Amplification | dB |
| Attenuation | 20 dB |
| Horizontal | 50 ns/div 1 |
| Vertical | 200 mV/div 1 |
| Horizontal | ns/div 2 |
| Vertical | mV/div 2 |
| Configuration | |
| Pulse Level | 30KV/charge |
| Data Link | |
| Comments: | |



(19)

FISCHER IN PLACE, USED BNC NON-SHORTING CAP FOR BACKGROUND.


| | |
|---------------|----------------|
| Date | August 9, 1985 |
| Test Point | |
| Amplification | dB |
| Attenuation | 20 dB |
| Horizontal | 50 ns/div 1 |
| Vertical | 200 mV/div 1 |
| Horizontal | 50 ns/div 2 |
| Vertical | 200 mV/div 2 |
| Configuration | |
| Pulse Level | 30KV/charge |
| Data Link | |
| Comments: | |



(20)

RE RUN OF (17) - ANTENNA, FISCHER, $I = +2A \cdot -6A$
 CONDUCTIVE TAPE OVER BNC CONNECTORS (2A/DIV)
 7.2A (360V)


| | | | |
|---------------|----------------|---|--|
| Date | August 9, 1985 | | |
| Test Point | | | |
| Amplification | dB | | |
| Attenuation | 20 dB | | |
| Horizontal | 50 ns/div | 1 | |
| Vertical | 200 mV/div | 1 | |
| Horizontal | 50 ns/div | 2 | |
| Vertical | 200 mV/div | 2 | |
| Configuration | | | |
| Pulse Level | 30KV charge | | |
| Data Link | | | |
| Comments: | | | |



(21)

RUBBER DUCK ANTENNA , BNC T, $I=5A$ PEAK
 (2 A/div) 5.6A (280V)


| | | | |
|---------------|----------------|---|--|
| Date | August 9, 1985 | | |
| Test Point | | | |
| Amplification | dB | | |
| Attenuation | 20 dB | | |
| Horizontal | 50 ns/div | 1 | |
| Vertical | 200 mV/div | 1 | |
| Horizontal | 50 ns/div | 2 | |
| Vertical | 200 mV/div | 2 | |
| Configuration | | | |
| Pulse Level | 30KV charge | | |
| Data Link | | | |
| Comments: | | | |




(22)

RUBBER DUCK ANTENNA - THROUGH GAS GAP
 PROTECTOR IN BNC T
 (2 A/div) - (5.6A) (280V)


| | | | |
|---------------|-----------------|---|--|
| Date | August 9, 1985 | | |
| Test Point | F18R | | |
| Amplification | dB | | |
| Attenuation | dB | | |
| Horizontal | 50 ns/div | 1 | |
| Vertical | 200 mV/div | 1 | |
| Horizontal | ns/div | 2 | |
| Vertical | mV/div | 2 | |
| Configuration | | | |
| Pulse Level | 30KV/charge | | |
| Date Link | | | |
| Comments: | (SYSTEM 7) (23) | | |
| | UNPROTECTED | | |




| | | | |
|---------------|------------------|---|--|
| Date | August 9, 1985 | | |
| Test Point | F19R | | |
| Amplification | dB | | |
| Attenuation | dB | | |
| Horizontal | 50 ns/div | 1 | |
| Vertical | 200 mV/div | 1 | |
| Horizontal | ns/div | 2 | |
| Vertical | mV/div | 2 | |
| Configuration | | | |
| Pulse Level | 30KV/charge | | |
| Date Link | | | |
| Comments: | (SYSTEM 13) (24) | | |



| | |
|---------------|---------------------|
| Date | August 9, 1985 |
| Test Point | F20R, F21R |
| Amplification | dB |
| Attenuation | dB |
| Horizontal | 50 ns/div 1 |
| Vertical | 200 mV/div 1 |
| Horizontal | ns/div 2 |
| Vertical | mV/div 2 |
| Configuration | |
| Pulse Level | 30KV charge |
| Date Link | |
| Comments: | (SYSTEMS 7 + 13) 25 |



| | |
|---------------|----------------|
| Date | August 9, 1985 |
| Test Point | F22T |
| Amplification | dB |
| Attenuation | dB |
| Horizontal | 50 ns/div 1 |
| Vertical | 200 mV/div 1 |
| Horizontal | ns/div 2 |
| Vertical | mV/div 2 |
| Configuration | |
| Pulse Level | 30KV charge |
| Date Link | |
| Comments: | (SYSTEM 13) 26 |



Date August 9, 1985

Test Point F23T

Amplification dB

Attenuation dB

Horizontal 50 ns/div 1

Vertical 200 mV/div 1

Horizontal ns/div 2

Vertical mV/div 2

Configuration


Pulse Level 30KV Charge

Data Link

Comments:

(SYSTEM 7)

(27)



Date August 9, 1985

Test Point F24R

Amplification dB

Attenuation dB

Horizontal 50 ns/div 1

Vertical 200 mV/div 1

Horizontal ns/div 2

Vertical mV/div 2

Configuration


Pulse Level 30KV Charge

Data Link


Comments:

(SYSTEM 7)


(28)



Date August 9, 1985
 Test Point F25R
 Amplification dB
 Attenuation dB
 Horizontal 50 ns/div 1
 Vertical 200 mV/div 1
 Horizontal ns/div 2
 Vertical mV/div 2
 Configuration
 Pulse Level 30 KV/charge
 Data Link
 Comments:
 (System 13) (29)




Date August 9, 1985
 Test Point F26
 Amplification dB
 Attenuation dB
 Horizontal 50 ns/div 1
 Vertical 200 mV/div 1
 Horizontal ns/div 2
 Vertical mV/div 2
 Configuration
 Pulse Level 30 KV/charge
 Data Link
 Comments:
 (SYSTEM 13)
 BATTERY CHARGER (30)



Date August 9, 1985
 Test Point F27
 Amplification dB
 Attenuation dB
 Horizontal 50 ns/div 1
 Vertical 200 mV/div 1
 Horizontal ns/div 2
 Vertical mV/div 2
 Configuration
 Pulsar Level 30KV Charge
 Data Link

Comments:


(SYSTEM 13)
 Battery Charger (31)



Date August 9, 1985
 Test Point F28
 Amplification dB
 Attenuation dB
 Horizontal 50 ns/div 1
 Vertical 200 mV/div 1
 Horizontal ns/div 2
 Vertical mV/div 2
 Configuration
 Pulsar Level 30KV Charge
 Data Link

Comments:

(SYSTEM 13)
 Battery Charger (32)




NO PHOTO 33

Date August 9, 1985
 Test Point F29
 Amplification dB
 Attenuation dB
 Horizontal 50 ns/div 1
 Vertical 200 mV/div 1
 Horizontal ns/div 2
 Vertical mV/div 2
 Configuration
 Pulse Level 30 KV charge
 Data Link

Comments:

(SYSTEM 13)

(34)




Date August 9, 1982
 Test Point F30
 Amplification dB
 Attenuation dB
 Horizontal 50 ns/div 1
 Vertical 200 mV/div 1
 Horizontal ns/div 2
 Vertical mV/div 2
 Configuration
 Pulse Level 30 KV charge
 Data Link


Comments:

(SYSTEM 7)


(35)



| | | | |
|---------------|----------------|---|--|
| Date | August 9, 1985 | | |
| Test Point | F31 | | |
| Amplification | dB | | |
| Attenuation | dB | | |
| Horizontal | 50 ns/div | 1 | |
| Vertical | 200 mV/div | 1 | |
| Horizontal | ns/div | 2 | |
| Vertical | mV/div | 2 | |
| Configuration | | | |
| Pulse Level | 30KV/charge | | |
| Data Link | | | |
| Comments: | (SYSTEM 7) | | |
| | (36) | | |




| | | | |
|---------------|----------------|---|--|
| Date | August 9, 1985 | | |
| Test Point | F32R | | |
| Amplification | dB | | |
| Attenuation | dB | | |
| Horizontal | 50 ns/div | 1 | |
| Vertical | 200 mV/div | 1 | |
| Horizontal | ns/div | 2 | |
| Vertical | mV/div | 2 | |
| Configuration | | | |
| Pulse Level | 30KV/charge | | |
| Data Link | | | |
| Comments: | (SYSTEM 12) | | |
| | (37) | | |




| | |
|---------------|----------------|
| Date | August 9, 1985 |
| Test Point | F32RL |
| Amplification | dB |
| Attenuation | dB |
| Horizontal | 50 ns/div 1 |
| Vertical | 200 mV/div 1 |
| Horizontal | ns/div 2 |
| Vertical | mV/div 2 |
| Configuration | |
| Pulse Level | 30 KV Charge |
| Data Link | |
| Comments: | (SYSTEM 12) |

(38)




| | |
|---------------|----------------|
| Date | August 9, 1985 |
| Test Point | F33R |
| Amplification | dB |
| Attenuation | dB |
| Horizontal | 50 ns/div 1 |
| Vertical | 200 mV/div 1 |
| Horizontal | ns/div 2 |
| Vertical | mV/div 2 |
| Configuration | |
| Pulse Level | 30 KV Charge |
| Data Link | |
| Comments: | (SYSTEM 12) |


(39)




Date August 9, 1985
 Test Point F33T
 Amplification dB
 Attenuation dB
 Horizontal 50 ns/div 1
 Vertical 200 mV/div 1
 Horizontal ns/div 2
 Vertical mV/div 2
 Configuration
 Pulse Level 30KV charge
 Data Link
 Comments:
(SYSTEM 12) (41)




Date August 9, 1985
 Test Point F34R
 Amplification dB
 Attenuation dB
 Horizontal 50 ns/div 1
 Vertical 200 mV/div 1
 Horizontal ns/div 2
 Vertical mV/div 2
 Configuration
 Pulse Level 30KV charge
 Data Link
 Comments:
(SYSTEM 6) (42)




| | | | |
|---------------|-----------------|--------|---|
| Date | August 9, 1985 | | |
| Test Point | F34T | | |
| Amplification | dB | | |
| Attenuation | dB | | |
| Horizontal | 50 | ns/div | 1 |
| Vertical | 200 | mV/div | 1 |
| Horizontal | | ns/div | 2 |
| Vertical | | mV/div | 2 |
| Configuration | | | |
| Pulse Level | 30KV charge | | |
| Data Link | | | |
| Comments: | (SYSTEM 6) (43) | | |




| | | | |
|---------------|-----------------|--------|---|
| Date | August 9, 1985 | | |
| Test Point | F35R | | |
| Amplification | dB | | |
| Attenuation | dB | | |
| Horizontal | 50 | ns/div | 1 |
| Vertical | 200 | mV/div | 1 |
| Horizontal | | ns/div | 2 |
| Vertical | | mV/div | 2 |
| Configuration | | | |
| Pulse Level | 30KV charge | | |
| Data Link | | | |
| Comments: | (SYSTEM 6) (44) | | |




| | | | |
|---------------|-----------------|--------|---|
| Date | August 9, 1985 | | |
| Test Point | F35T | | |
| Amplification | dB | | |
| Attenuation | dB | | |
| Horizontal | 50 | ns/div | 1 |
| Vertical | 200 | mV/div | 1 |
| Horizontal | | ns/div | 2 |
| Vertical | | mV/div | 2 |
| Configuration | | | |
| Pulse Level | 30KV/Charge | | |
| Date Link | | | |
| Comments: | (SYSTEM 6) (45) | | |




| | | | |
|---------------|-----------------|--------|---|
| Date | August 9, 1985 | | |
| Test Point | F36R | | |
| Amplification | dB | | |
| Attenuation | dB | | |
| Horizontal | 50 | ns/div | 1 |
| Vertical | 200 | mV/div | 1 |
| Horizontal | | ns/div | 2 |
| Vertical | | mV/div | 2 |
| Configuration | | | |
| Pulse Level | 30KV/Charge | | |
| Date Link | | | |
| Comments: | (SYSTEM 8) (46) | | |



| | |
|---------------|-----------------|
| Date | August 9, 1985 |
| Test Point | F36T |
| Amplification | dB |
| Attenuation | dB |
| Horizontal | 50 ns/div 1 |
| Vertical | 200 mV/div 1 |
| Horizontal | ns/div 2 |
| Vertical | mV/div 2 |
| Configuration | |
| Pulse Level | 30 KV Charge |
| Date Link | |
| Comments: | (SYSTEM 8) (47) |



| | |
|---------------|-----------------|
| Date | August 9, 1985 |
| Test Point | F37R |
| Amplification | dB |
| Attenuation | dB |
| Horizontal | 50 ns/div 1 |
| Vertical | 200 mV/div 1 |
| Horizontal | ns/div 2 |
| Vertical | mV/div 2 |
| Configuration | |
| Pulse Level | 30 KV Charge |
| Date Link | |
| Comments: | (SYSTEM 8) (48) |




Date August 9, 1985
 Test Point F37R1
 Amplification dB
 Attenuation dB
 Horizontal 50 ns/div 1
 Vertical 200 mV/div 1
 Horizontal ns/div 2
 Vertical mV/div 2
 Configuration
 Pulse Level 30KV charge
 Data Link

Comments:

(SYSTEM 8)

(49)




Date August 9, 1985
 Test Point F37T
 Amplification dB
 Attenuation dB
 Horizontal 50 ns/div 1
 Vertical 200mV/div 1
 Horizontal ns/div 2
 Vertical mV/div 2
 Configuration
 Pulse Level 30KV charge
 Data Link

Comments:

(SYSTEM 8)


(50)



Date August 9, 1985
 Test Point F38R
 Amplification dB
 Attenuation dB
 Horizontal 50 ns/div 1
 Vertical 200 mV/div 1
 Horizontal ns/div 2
 Vertical mV/div 2
 Configuration
 Pulse Level 30KV charge
 Data Link
 Comments:

SYSTEM 9

(51)




Date August 9, 1985
 Test Point F38T
 Amplification dB
 Attenuation dB
 Horizontal 50 ns/div 1
 Vertical 200 mV/div 1
 Horizontal ns/div 2
 Vertical mV/div 2
 Configuration
 Pulse Level 30KV charge
 Data Link

Comments:

(SYSTEM 9)

(52)



Date August 9, 1985

Test Point F39R

Amplification dB

Attenuation dB

Horizontal 50 ns/div 1

Vertical 200 mV/div 1

Horizontal ns/div 2

Vertical mV/div 2

Configuration


Pulse Level 30KV/charge

Date Link

Comments:

(SYSTEM 9)

(53)



Date August 9, 1985

Test Point F39RL

Amplification dB

Attenuation dB

Horizontal 50 ns/div 1

Vertical 200 mV/div 1

Horizontal ns/div 2

Vertical mV/div 2

Configuration


Pulse Level 30KV/charge

Date Link


Comments:

(SYSTEM 9)


(54)




| | |
|---------------|-----------------|
| Date | August 9, 1985 |
| Test Point | F39T |
| Amplification | dB |
| Attenuation | dB |
| Horizontal | 50 ns/div 1 |
| Vertical | 200 mV/div 1 |
| Horizontal | ns/div 2 |
| Vertical | mV/div 2 |
| Configuration | |
| Pulse Level | 30KV charge |
| Data Link | |
| Comments: | (SYSTEM 9) (55) |




| | |
|---------------|----------------------|
| Date | August 9, 1985 |
| Test Point | F40 |
| Amplification | dB |
| Attenuation | dB |
| Horizontal | 50 ns/div 1 |
| Vertical | 200mV/div 1 |
| Horizontal | ns/div 2 |
| Vertical | mV/div 2 |
| Configuration | |
| Pulse Level | 30KV charge |
| Data Link | |
| Comments: | DC POWER SUPPLY (56) |



| | |
|----------------------|----------------|
| Date | August 9, 1985 |
| Test Point | F41 |
| Amplification | dB |
| Attenuation | dB |
| Horizontal | 50 ns/div 1 |
| Vertical | 200 mV/div 1 |
| Horizontal | ns/div 2 |
| Vertical | mV/div 2 |
| Configuration | |
| Pulse Level | 30KV Charge |
| Data Link | |
| Comments: | |
| DC POWER SUPPLY (57) | |



| | |
|---------------|----------------|
| Date | August 9, 1985 |
| Test Point | F42 |
| Amplification | dB |
| Attenuation | dB |
| Horizontal | 50 ns/div 1 |
| Vertical | 200 mV/div 1 |
| Horizontal | ns/div 2 |
| Vertical | mV/div 2 |
| Configuration | |
| Pulse Level | 30KV Charge |
| Data Link | |
| Comments: | |
| HONDA (58) | |




Date August 9, 1985
 Test Point F43
 Amplification dB
 Attenuation dB
 Horizontal 50 ns/div 1
 Vertical 200 mV/div 1
 Horizontal ns/div 2
 Vertical mV/div 2
 Configuration
 Pulsar Level 30KV Charge
 Data Link

Comments:

HONDA

(59)




Date August 9, 1985
 Test Point F44
 Amplification dB
 Attenuation dB
 Horizontal 50 ns/div 1
 Vertical 200 mV/div 1
 Horizontal ns/div 2
 Vertical mV/div 2
 Configuration
 Pulsar Level 30KV Charge
 Data Link


Comments:

HONDA


(60)




| | | | |
|---------------|----------------|---|--|
| Date | August 9, 1985 | | |
| Test Point | F45 | | |
| Amplification | dB | | |
| Attenuation | dB | | |
| Horizontal | 50 ns/div | 1 | |
| Vertical | 200 mV/div | 1 | |
| Horizontal | ns/div | 2 | |
| Vertical | mV/div | 2 | |
| Configuration | | | |
| Pulse Level | 30 KV Charge | | |
| Data Link | | | |
| Comments: | HONDA (61) | | |




| | | | |
|---------------|----------------|---|--|
| Date | August 9, 1985 | | |
| Test Point | F46 | | |
| Amplification | dB | | |
| Attenuation | dB | | |
| Horizontal | 50 ns/div | 1 | |
| Vertical | 200 mV/div | 1 | |
| Horizontal | ns/div | 2 | |
| Vertical | mV/div | 2 | |
| Configuration | | | |
| Pulse Level | 30 KV Charge | | |
| Data Link | | | |
| Comments: | (62) | | |



| | | | |
|---------------|-------------------------------|---|--|
| Date | 9 August 1985 | | |
| Test Point | F47R | | |
| Amplification | dB | | |
| Attenuation | dB | | |
| Horizontal | 50 ns/div | 1 | |
| Vertical | 200 mV/div | 1 | |
| Horizontal | ns/div | 2 | |
| Vertical | mV/div | 2 | |
| Configuration | | | |
| Pulse Level | 30KV Charge | | |
| Date Link | | | |
| Comments: | (SYSTEM II) (+ HONDA) (63) | | |



| | | | |
|---------------|-------------------------------|---|--|
| Date | August 9, 1985 | | |
| Test Point | F47T | | |
| Amplification | dB | | |
| Attenuation | dB | | |
| Horizontal | 50 ns/div | 1 | |
| Vertical | 200 mV/div | 1 | |
| Horizontal | ns/div | 2 | |
| Vertical | mV/div | 2 | |
| Configuration | | | |
| Pulse Level | 30KV Charge | | |
| Date Link | | | |
| Comments: | (SYSTEM II) (+ HONDA) (64) | | |



END

FILMED

386

DTIC